


# 東芝照明器具配光データシート

名称	蛍光灯器具
形名	FRX-4404K

保守率	良	0.70
	中	0.66
	否	0.61



光源	名称	蛍光灯ランプ
	形名	FLR40S・W/M
	光束	3000 lm × 4

効率	F ◡	0%
	F ◣	60%
	F ○	60%
	器具光束	7205 lm

最大取付間隔	
A-A	1.2 H
B-B	1.3 H

備考	
----	--

前面	乳白アクリルカバー
反射面	塗装 (白)

光度 (cd/1000lm)			
θ \ φ	A-A	B-B	C-C
0°	210	210	210
10°	206	206	206
20°	195	196	195
30°	177	179	177
40°	152	156	154
50°	124	128	125
60°	92	95	93
70°	56	59	57
80°	22	23	23
90°	0	0	0
100°	0	0	0
110°	0	0	0
120°	0	0	0
130°	0	0	0
140°	0	0	0
150°	0	0	0
160°	0	0	0
170°	0	0	0
180°	0	0	0

反射率 (%)	天井		80		70		50		30		20		0							
	壁	床	70	50	30	70	50	30	50	30	30	10	10	0						
室指数	照明率 (×0.01)																			
0.60	37	34	29	27	24	23	36	34	28	27	23	23	28	26	23	23	23	22	20	19
0.80	45	41	36	34	31	29	43	40	36	34	30	29	34	33	30	29	29	29	26	25
1.00	49	44	41	38	35	33	48	43	40	37	35	33	38	36	34	33	33	32	29	28
1.25	54	48	46	42	40	38	52	47	45	42	40	37	43	40	38	37	37	36	34	32
1.50	57	50	49	45	44	41	55	49	48	44	43	40	46	43	42	40	40	39	37	35
2.00	62	54	55	50	50	46	60	53	54	49	49	46	51	48	47	45	46	44	42	40
2.50	65	56	59	52	54	49	62	55	57	51	53	49	54	50	51	48	49	47	45	43
3.00	67	57	62	54	58	51	65	56	60	53	56	51	57	52	54	50	51	49	47	46
4.00	70	59	66	57	62	54	67	58	64	56	60	54	60	55	57	53	55	52	50	49
5.00	71	60	68	58	65	56	69	59	66	58	63	56	62	56	60	55	57	54	52	51
10.00	75	63	73	62	71	60	72	62	70	61	69	60	66	59	65	59	61	57	56	55

