

東芝ランプ 配光データシート

名称	ネオボールZ
形名	EFA15EL/12-R
光束	810 lm × 1

保守率	良	0.74
	中	0.70
	否	0.62

--	--

効率	F	%
	F	%
	F	100 %
	器具光束	810 lm

最大取付間隔	
A-A	1.9 H
B-B	1.9 H

備考

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	63		
10°	65		
20°	68		
30°	73		
40°	79		
50°	85		
60°	89		
70°	93		
80°	95		
90°	94		
100°	92		
110°	85		
120°	79		
130°	69		
140°	60		
150°	48		
160°	39		
170°	25		
180°	0		

反射率 (%)	天井		80			70			50			30		20		0				
	壁	床	70	50	30	70	50	30	50	30	50	30	30	10	10	0				
室指数	照明率 (×0.01)																			
0.60	49	45	34	32	25	25	44	41	31	30	23	23	26	25	20	19	16	16	11	7
0.80	58	53	43	40	33	32	53	48	39	37	31	30	33	31	26	25	21	21	15	10
1.00	65	58	50	46	39	37	59	53	45	42	36	35	38	36	30	29	25	24	18	13
1.25	72	64	57	52	47	44	65	59	52	48	43	40	43	41	36	34	29	28	22	16
1.50	77	67	62	57	52	48	69	62	57	52	48	45	47	44	40	38	33	32	25	18
2.00	85	74	72	64	62	56	77	68	65	59	57	52	54	50	47	44	38	37	30	22
2.50	89	77	78	69	68	61	81	71	71	64	62	57	58	54	52	49	42	41	33	25
3.00	93	80	82	72	73	65	84	74	75	67	67	61	62	57	56	52	46	44	36	28
4.00	98	84	89	77	81	71	89	77	81	72	74	66	67	61	62	57	50	48	41	32
5.00	101	86	93	80	86	75	92	80	85	75	79	70	70	64	65	60	53	51	43	34
10.00	109	91	104	87	99	84	99	85	95	82	90	79	78	70	75	68	61	58	51	41

