

東芝ランプ 配光データシート

名称	LED電球 (ミニクリプトン形)
形名	LDA5L-E17
光束	410 lm × 1

保守率	良	1.00
	中	1.00
	否	1.00

--	--

効率	F		%
	F		%
	F	100	%
	器具光束	410	lm

最大取付間隔	
A-A	1.3 H
B-B	1.3 H

備考	
----	--

光度 (cd/1000lm)			
θ \ φ	A-A	B-B	C-C
0°	298		
10°	300		
20°	294		
30°	271		
40°	237		
50°	195		
60°	148		
70°	106		
80°	72		
90°	46		
100°	29		
110°	18		
120°	11		
130°	7		
140°	1		
150°	1		
160°	0		
170°	0		
180°	0		

反射率 (%)	天井						70						50						30						20						0																																																																																																																																																																																													
	壁		70		50		30		70		50		30		50		30		30		10		30		10		30		10		10		0																																																																																																																																																																																											
室指数	照明率 (×0.01)																																																																																																																																																																																																																											
0.60	63	58	47	44	37	36	60	56	45	43	36	35	43	41	35	34	33	33	27	25	74	68	58	54	47	45	71	65	56	53	46	45	53	51	44	43	43	42	36	33	84	76	68	63	57	54	81	73	66	62	56	53	62	59	53	51	51	49	44	41	92	82	77	70	66	62	88	79	74	69	64	61	70	66	61	58	58	56	51	47	99	87	84	76	73	68	94	84	81	74	71	67	76	71	67	64	64	62	56	53	108	94	94	84	84	77	103	91	91	82	82	75	85	79	77	73	73	70	65	61	113	98	101	90	92	83	108	95	98	88	89	81	90	84	83	78	78	75	70	67	117	100	107	93	98	87	112	98	102	91	95	86	95	87	88	82	83	79	74	71	122	104	114	98	106	93	117	101	109	96	102	91	100	92	95	88	89	85	80	76	126	106	118	101	112	97	120	104	113	99	107	95	104	95	100	91	93	88	84	80	133	111	128	108	124	106	127	109	123	106	119	104	112	102	101	00	101	96	92	88

