

東芝ランプ 配光データシート

名称	LED電球
形名	LDA6N/4
光束	485 lm × 1

保守率	良	1.00
	中	1.00
	否	1.00



効率	F	%
	F	%
	F	100 %
	器具光束	485 lm

最大取付間隔	
A-A	1.3 H
B-B	1.3 H

備考

光度 (cd/1000lm)			
θ	ϕ	A-A	B-B C-C
0°		258	
10°		254	
20°		243	
30°		226	
40°		203	
50°		175	
60°		142	
70°		107	
80°		75	
90°		49	
100°		31	
110°		19	
120°		12	
130°		8	
140°		2	
150°		1	
160°		0	
170°		0	
180°		0	

反射率 (%)	天井	80						70						50						30		20		0	
	壁	70	50	30	70	50	30	70	50	30	50	30	50	30	30	10	0								
床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0								
室指数	照明率 (×0.01)																								
0.60	57	52	41	39	32	31	54	50	40	38	31	31	38	36	30	29	29	28	23	21					
0.80	67	61	52	48	42	40	64	59	50	47	41	39	47	45	39	38	37	36	31	28					
1.00	76	68	61	56	50	48	73	66	59	55	49	47	55	52	47	45	44	43	38	35					
1.25	83	74	69	63	58	55	80	72	66	61	57	54	62	58	54	51	51	49	44	41					
1.50	89	79	75	68	65	60	85	76	73	67	63	59	67	63	60	57	56	54	49	46					
2.00	98	85	85	76	75	69	93	82	82	74	73	67	76	70	68	65	64	62	57	53					
2.50	103	89	92	81	82	74	98	86	88	79	80	73	81	75	74	70	70	67	62	58					
3.00	107	91	97	85	88	79	101	89	92	82	85	77	85	78	79	74	74	71	66	62					
4.00	112	95	103	89	96	84	106	92	99	87	92	82	91	83	85	79	79	76	71	67					
5.00	115	97	107	92	101	88	109	94	103	90	97	86	94	86	90	82	83	79	75	71					
10.00	122	102	117	99	113	96	116	99	112	97	108	94	102	92	99	90	91	86	83	79					

