

東芝照明器具配光データシート

名称	蛍光灯器具
形名	FB2342NEB

保守率	良	0.78
	中	0.74
	否	0.70

最大取付間隔	
A-A	1.3 H
B-B	1.8 H

光源	名称	蛍光ランプ
	形名	FL20SSEXN18Z
	光束	1550 lm × 1

効率	F	21%
	F	46%
	F	67%
	器具光束	1030 lm

備考	
----	--

前面	グローブ (乳白)
反射面	

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	80	80	80
10°	80	81	82
20°	78	91	85
30°	72	97	88
40°	63	101	89
50°	53	102	87
60°	42	99	82
70°	30	93	75
80°	17	86	66
90°	10	78	58
100°	10	73	54
110°	9	66	48
120°	9	57	40
130°	8	46	31
140°	8	34	22
150°	8	21	13
160°	0	0	0
170°	0	0	0
180°	0	0	0

反射率 (%)	天井	80						70						50						30		20		0	
	壁	70	50	30	70	50	30	70	50	30	50	30	50	30	30	10	0	10	0						
室指数	照明率 (×0.01)																								
0.60	34	31	24	23	18	18	32	29	23	22	17	17	20	19	16	15	14	14	10	8					
0.80	41	37	31	29	24	23	38	35	29	27	23	22	26	24	21	20	18	18	14	12					
1.00	46	41	36	33	29	27	42	38	33	31	27	26	29	28	24	23	21	21	17	14					
1.25	51	45	41	37	34	32	47	42	38	35	32	30	33	31	28	27	25	24	20	17					
1.50	54	47	44	40	37	35	50	44	42	38	35	33	36	34	31	30	28	27	23	19					
2.00	59	52	51	45	44	40	55	49	47	43	42	38	41	38	37	35	32	31	27	23					
2.50	62	54	55	48	49	44	58	51	51	46	46	42	44	41	40	38	35	34	30	25					
3.00	65	56	58	51	52	47	60	53	54	48	49	44	47	43	43	40	38	36	32	27					
4.00	68	58	62	54	57	50	63	55	58	51	54	48	50	46	47	43	41	39	35	30					
5.00	70	60	65	56	61	53	65	56	61	53	57	50	53	48	50	46	43	41	37	32					
10.00	75	63	72	61	69	59	70	60	67	58	64	56	58	52	56	51	48	46	42	37					

