



# 東芝照明器具配光データシート

名 称	LEDダウンライト
形 名	LEDD-95011N-LD9

効 率	F	0 %
	F	100 %
	F	100 %
	器具光束	8800 lm

保守率	良	0.67
	中	0.63
	否	0.56

 $\theta$  $\phi$ 

前 面	下面開放
反射面	梨地処理

最大取付間隔	
A-A	1.2 H
B-B	1.2 H

備 考

光度 (cd/1000lm)				反 射 率 (%)	天井		80		70		50		30		20		0							
$\theta \setminus \phi$					壁	70	50	30	70	50	30	50	30	30	10	0								
	A-A	B-B	C-C		床	30	10	30	10	30	10	30	10	30	10	30	10	0						
0°	633				室指数 固有照明率 (×0.01)																			
10°	604			0.60	78	72	67	63	60	58	76	71	66	63	59	58	64	62	59	57	58	57	54	52
20°	570			0.80	91	82	80	75	73	70	89	81	79	75	73	70	77	74	71	69	70	69	66	64
30°	511			1.00	97	87	86	80	79	75	94	86	85	79	78	75	82	78	77	74	76	74	71	69
40°	336			1.25	103	91	93	85	86	81	100	90	91	85	85	80	88	83	83	80	81	79	76	74
50°	115			1.50	107	94	98	89	91	85	104	93	96	88	90	84	92	87	87	83	85	82	80	78
60°	37			2.00	113	98	105	94	99	91	110	97	103	93	97	90	99	92	94	89	91	88	85	84
70°	6			2.50	116	100	109	97	104	94	113	99	107	96	102	93	102	94	98	92	94	90	88	87
80°	2			3.00	118	102	112	99	108	96	115	100	110	98	105	95	104	96	101	94	97	92	90	89
90°	0			4.00	121	103	117	101	112	99	117	102	113	100	110	98	107	98	104	96	100	95	93	91
100°	0			5.00	123	104	119	102	115	100	119	103	116	101	112	100	109	99	107	98	101	96	95	93
110°	0			10.00	127	106	125	105	122	104	122	105	120	104	118	103	113	102	111	101	105	99	98	96
120°	0																							
130°	0																							
140°	0																							
150°	0																							
160°	0																							
170°	0																							
180°	0																							

