

# 東芝ランプ 配光データシート

名称	LED電球 ミニクリ形
形名	LDA6N-D-H-E 17/S
光束	440 lm × 1

保守率	良	1.00
	中	1.00
	否	1.00



効率	F	%
	F	%
	F	100 %
	器具光束	440 lm

最大取付間隔	
A-A	1.3 H
B-B	1.3 H

備考  
データは初期の標準値です。

光度 (cd/1000lm)			
$\theta$	$\phi$	A-A	B-B C-C
0°		275	
10°		271	
20°		257	
30°		235	
40°		206	
50°		172	
60°		136	
70°		101	
80°		70	
90°		46	
100°		30	
110°		19	
120°		12	
130°		7	
140°		1	
150°		1	
160°		0	
170°		0	
180°		0	

反射率 (%)	天井	80						70						50						30		20		0						
	壁	70	50	30	70	50	30	70	50	30	50	30	50	30	30	10	0													
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0
室指数	照明率 (×0.01)																													
0.60	59	54	44	42	35	34	56	52	43	41	35	34	41	39	33	33	32	31	27	25										
0.80	70	64	55	52	46	44	67	62	54	51	45	43	51	48	43	42	41	40	35	33										
1.00	77	69	63	58	53	50	74	67	61	57	52	49	57	54	49	47	47	46	41	38										
1.25	85	75	71	65	61	57	81	73	68	63	59	56	64	60	56	54	53	52	47	44										
1.50	90	79	76	69	67	62	86	77	74	68	65	61	69	64	61	58	58	56	51	48										
2.00	98	85	86	77	77	70	93	83	83	75	75	69	77	72	70	66	66	64	59	55										
2.50	103	89	92	81	83	75	98	86	89	79	81	74	82	76	76	71	71	68	63	60										
3.00	106	91	97	85	89	79	101	89	93	83	86	78	86	79	80	75	75	72	67	64										
4.00	111	95	103	89	96	85	106	92	99	87	93	83	91	83	86	80	80	76	72	69										
5.00	114	97	107	92	101	88	109	94	103	90	97	86	94	86	90	83	84	79	75	72										
10.00	121	101	117	98	113	96	115	99	111	96	108	94	102	92	99	90	91	86	83	79										

