

# 東芝ランプ 配光データシート

名称	LEDライトエンジン
形名	LECF/14L-W1 3GH3085
光束	1360 lm × 1

保守率	良	1.00
	中	1.00
	否	1.00



効率	F	%
	F	%
	F	100 %
	器具光束	1360 lm

最大取付間隔	
A-A	1.1 H
B-B	1.1 H

備考  
データは初期の標準値です。

光度 (cd/1000lm)		A-A	B-B	C-C
0°	φ	490		
10°		480		
20°		435		
30°		351		
40°		246		
50°		151		
60°		109		
70°		69		
80°		34		
90°		8		
100°		7		
110°		6		
120°		5		
130°		4		
140°		3		
150°		1		
160°		0		
170°		0		
180°		0		

反射率 (%)	天井	80						70						50						30						20						0																
	壁	70		50		30		70		50		30		50		30		30		10		0		30		10		0		10		0																
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10													
室指数	照明率 (×0.01)																																															
0.60	65	60	51	49	43	42	63	58	50	48	42	41	49	47	42	41	41	40	36	34																												
0.80	76	69	62	58	53	51	73	67	61	57	53	51	58	56	51	50	50	49	44	43																												
1.00	85	76	71	66	62	59	82	74	70	65	61	59	67	63	60	58	58	57	52	50																												
1.25	92	81	79	73	70	66	89	80	77	71	69	65	74	69	67	64	65	63	58	56																												
1.50	97	86	85	77	77	71	94	84	83	76	75	70	79	74	72	69	70	68	63	61																												
2.00	105	91	94	84	86	79	101	89	92	83	84	78	87	81	81	76	77	75	71	68																												
2.50	109	94	100	88	93	83	105	92	97	87	90	83	91	85	86	81	82	79	75	73																												
3.00	112	96	104	91	98	87	108	95	101	90	95	86	95	87	90	84	86	82	79	76																												
4.00	117	99	110	95	104	92	112	97	106	94	101	91	100	91	96	88	91	86	83	81																												
5.00	119	101	114	98	109	95	115	99	110	96	105	93	103	93	99	91	94	89	86	84																												
10.00	125	104	122	103	119	101	120	103	117	101	115	100	109	98	107	97	100	95	92	90																												

