


# 東芝照明器具配光データシート

名称	ユニバーサルダウンライト
形名	LEDD-10103W W-LD9

保守率	良	0.90
	中	0.86
	否	0.76



光源	名称	LED
	形名	LED
	光束	1600 lm × 1

効率	F	0%
	F	100%
	F	100%
	器具光束	1600 lm

最大取付間隔	
A-A	0.6 H
B-B	0.6 H

備考	
----	--

前面	
反射面	

光度 (cd/1000lm)			
0°	2302	25°	483
1°		30°	261
2°		35°	143
3°		40°	85
4°		45°	56
5°	2219	50°	40
6°		55°	29
7°		60°	22
8°		65°	16
9°		70°	11
10°	1851	75°	6
11°		80°	2
12°		85°	0
13°		90°	0
14°			
15°	1378		
16°			
17°			
18°			
19°			
20°	859		

反射率 (%)	天井	80				70				50				30		20	0			
	壁	70	50	30	70	50	30	50	30	50	30	30	10	0						
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0			
室指数		照明率 (×0.01)																		
0.60	88	81	78	74	72	70	86	80	77	74	72	70	76	73	71	69	70	69	67	66
0.80	96	87	86	81	80	77	94	86	85	81	80	77	84	80	79	76	78	76	73	72
1.00	102	92	93	86	87	83	100	91	92	86	86	82	89	85	85	82	83	81	79	77
1.25	106	94	98	89	91	86	104	93	96	89	90	85	93	88	88	85	86	84	81	80
1.50	109	96	101	92	95	88	107	95	99	91	94	88	96	90	91	87	89	86	84	82
2.00	114	99	106	95	101	92	111	98	104	94	99	91	100	93	96	90	93	89	87	85
2.50	117	101	110	97	105	95	113	100	108	97	103	94	103	95	99	93	95	91	89	88
3.00	119	102	113	99	108	97	115	101	110	98	106	96	105	97	102	95	98	93	91	90
4.00	122	104	118	102	114	100	118	103	114	101	111	99	108	99	106	98	101	96	94	93
5.00	124	105	121	104	117	102	120	104	117	103	114	101	110	101	108	100	103	98	96	95
10.00	129	108	127	107	126	107	124	106	123	106	122	106	115	104	114	104	108	102	101	99

