

東芝ランプ 配光データシート

名称	LEDユニットフラット
形名	LDF5N-W-GX5 3/3
光束	450 lm × 1

保守率	良	1.00
	中	1.00
	否	1.00



効率	F		%
	F		%
	F	100	%
	器具光束	450	lm

最大取付間隔	
A-A	0.7 H
B-B	0.7 H

備考
データは初期の標準値です。

θ	φ	光度 (cd/1000lm)		
		A-A	B-B	C-C
0°		1070		
10°		975		
20°		627		
30°		360		
40°		205		
50°		99		
60°		61		
70°		42		
80°		26		
90°		10		
100°		0		
110°		0		
120°		0		
130°		0		
140°		0		
150°		0		
160°		0		
170°		0		
180°		0		

反射率 (%)	天井	80				70				50				30		20		0		
	壁	70		50		30		70		50		30		50		30		10		0
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0	
室指数	照明率 (×0.01)																			
0.60	75	69	63	60	55	54	73	68	62	59	55	53	60	58	54	53	53	52	49	47
0.80	85	77	73	68	65	62	83	76	72	68	65	62	70	67	63	61	62	61	57	56
1.00	93	84	81	76	73	70	91	82	80	75	73	69	77	73	71	69	70	68	64	63
1.25	99	88	88	81	80	75	96	87	86	80	79	75	83	78	77	74	75	73	69	68
1.50	103	91	93	85	85	79	100	90	91	84	84	79	87	82	82	78	79	77	73	71
2.00	110	95	101	90	93	85	106	94	98	89	92	85	94	87	88	83	85	82	79	77
2.50	114	98	106	93	99	89	110	97	103	92	97	88	98	90	93	87	89	86	83	81
3.00	116	100	109	96	103	92	113	98	106	95	101	91	101	93	96	90	92	88	85	83
4.00	120	102	114	99	109	96	116	101	111	98	106	95	105	96	101	93	96	92	89	87
5.00	123	104	118	101	113	99	118	102	114	100	110	98	107	98	104	96	99	94	92	90
10.00	128	107	125	105	122	104	123	105	121	104	118	103	113	102	111	101	105	99	97	95

