

東芝照明器具配光データシート

名称	LED照明器具
形名	LEDG87940L (W) -LSX

--	--

効 率	F	0 %
	F	100 %
	F	100 %
	器具光束	480 lm

保守率	良	0.67
	中	0.63
	否	0.56

前面	
反射面	

最大取付間隔	
A-A	1.2 H
B-B	1.2 H

備 考	
--------	--

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	424		
10°	417		
20°	394		
30°	333		
40°	269		
50°	197		
60°	136		
70°	76		
80°	19		
90°	0		
100°	0		
110°	0		
120°	0		
130°	0		
140°	0		
150°	0		
160°	0		
170°	0		
180°	0		

反射率 (%)	天井	80						70						50						30		20		0	
	壁	70		50		30		70		50		30		50		30		30		10		0			
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0	0
室指数	固有照明率 (×0.01)																								
0.60	66	61	53	50	45	43	65	60	52	50	44	43	50	48	43	42	43	42	38	36					
0.80	79	72	65	61	57	54	77	70	64	61	56	54	62	59	55	53	54	53	49	47					
1.00	86	77	73	67	64	61	83	76	71	67	63	60	69	65	62	59	60	59	54	53					
1.25	93	83	81	74	72	68	90	81	79	73	71	67	76	72	69	66	67	65	61	59					
1.50	98	86	86	78	78	72	95	85	85	78	77	72	81	76	74	71	72	70	66	64					
2.00	106	92	96	86	88	80	102	91	94	85	86	80	89	83	83	79	80	77	74	72					
2.50	110	95	102	90	94	85	107	94	99	89	92	84	94	87	89	83	85	82	78	76					
3.00	114	97	106	93	99	89	110	96	103	92	97	88	97	90	93	86	89	85	82	80					
4.00	118	100	112	97	106	93	114	99	108	95	103	92	102	93	98	91	94	89	87	85					
5.00	120	102	115	99	110	96	116	100	112	98	107	95	105	96	102	93	97	92	89	87					
10.00	126	105	123	104	120	102	121	104	119	102	116	101	111	100	109	99	103	97	95	93					

