

東芝照明器具配光データシート

名称	LED照明器具
形名	LEDG87941YL (S) -LSX

--	--

効 率	F	0 %
	F	100 %
	F	100 %
	器具光束	450 lm

保守率	良	0.67
	中	0.63
	否	0.60

前面	
反射面	

最大取付間隔	
A-A	1.2 H
B-B	1.2 H

備 考	
--------	--

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	459		
10°	454		
20°	428		
30°	359		
40°	290		
50°	200		
60°	121		
70°	50		
80°	8		
90°	1		
100°	0		
110°	0		
120°	0		
130°	0		
140°	0		
150°	0		
160°	0		
170°	0		
180°	0		

反射率 (%)	天井	80			70			50			30		20	0						
	壁	70	50	30	70	50	30	50	30	30	10	0								
床	30	10	30	10	30	10	30	10	30	10	30	10	0							
室指数	固有照明率 (×0.01)																			
0.60	68	63	55	53	47	46	67	62	55	52	47	46	53	51	46	45	46	45	41	39
0.80	81	74	68	64	60	58	79	72	67	64	60	57	65	62	58	57	57	56	52	50
1.00	88	79	76	70	67	64	86	78	74	69	66	63	72	68	65	63	64	62	58	56
1.25	95	85	84	77	75	71	93	83	82	76	74	70	79	74	72	69	70	68	65	63
1.50	100	88	89	81	81	75	97	87	87	80	80	75	84	78	78	74	75	73	69	67
2.00	108	94	98	88	91	83	104	92	96	87	89	82	92	85	86	81	83	80	77	75
2.50	112	97	104	92	97	87	108	95	101	91	95	87	96	89	91	85	88	84	81	79
3.00	115	99	108	94	102	91	111	97	105	93	99	90	99	91	95	88	91	87	84	82
4.00	119	101	113	98	108	95	115	100	110	97	105	94	104	95	100	92	95	91	88	87
5.00	121	103	116	100	112	97	117	101	113	99	109	97	106	97	103	95	98	93	91	89
10.00	126	105	123	104	121	103	122	104	119	103	117	102	112	101	110	100	104	98	96	94

