

# 東芝ランプ 配光データシート

名称	東芝LED電球
形名	LDA8L-G-K/D /50W
光束	640 lm × 1

保守率	良	1.00
	中	1.00
	否	1.00



効率	F		%
	F		%
	F	100	%
	器具光束	640	lm

最大取付間隔	
A-A	1.4 H
B-B	1.4 H

備考

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	150		
10°	150		
20°	148		
30°	144		
40°	138		
50°	131		
60°	121		
70°	110		
80°	97		
90°	83		
100°	69		
110°	54		
120°	40		
130°	28		
140°	17		
150°	8		
160°	3		
170°	0		
180°	0		

反射率 (%)	天井	80						70						50						30						20						0					
	壁	70		50		30		70		50		30		50		30		30		10		30		10		10		0									
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10								
室指数	照明率 (×0.01)																																				
0.60	53	49	38	36	29	28	50	46	36	34	28	27	32	31	25	25	23	22	17	14																	
0.80	63	57	48	45	38	36	59	54	45	43	36	35	41	39	33	32	30	29	24	20																	
1.00	70	63	55	51	44	42	66	60	52	48	42	40	46	44	38	37	35	34	28	24																	
1.25	78	69	63	57	52	49	73	65	59	55	49	47	53	50	45	43	40	39	33	29																	
1.50	83	73	68	62	58	53	77	69	64	59	55	51	57	54	49	47	44	43	37	32																	
2.00	91	79	78	70	68	62	85	75	73	66	64	59	65	60	58	54	52	50	43	38																	
2.50	96	83	84	74	74	67	89	79	79	71	70	64	70	64	63	59	56	54	48	42																	
3.00	100	85	89	78	80	71	93	81	84	74	76	68	74	68	67	63	60	57	51	46																	
4.00	105	89	96	83	88	77	98	85	90	79	83	74	79	72	74	68	65	62	56	50																	
5.00	108	91	100	86	93	81	101	87	94	82	88	78	82	75	78	71	69	65	60	53																	
10.00	115	96	111	93	106	90	108	92	103	89	99	86	91	82	88	80	77	73	68	61																	

