

東芝照明器具配光データシート

名称	LED照明器具
形名	LEDB87045YL-LSX

--	--

効 率	F	25%
	F	75%
	F	100%
	器具光束	340 lm

保守率	良	0.63
	中	0.60
	否	0.56

前面	
反射面	

最大取付間隔	
A-A	1.5 H
B-B	1.5 H

備 考	
--------	--

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	153		
10°	160		
20°	161		
30°	154		
40°	142		
50°	127		
60°	111		
70°	90		
80°	68		
90°	51		
100°	49		
110°	47		
120°	38		
130°	31		
140°	24		
150°	19		
160°	13		
170°	5		
180°	0		

反射率 (%)	天井	80						70						50						30		20		0	
	壁	70	50	30	70	50	30	70	50	30	50	30	50	30	30	10	0								
床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0								
室指数	固有照明率 (×0.01)																								
0.60	54	50	40	38	31	30	51	47	38	36	30	29	34	33	27	27	25	25	20	17					
0.80	65	59	50	47	41	39	61	56	48	45	39	37	43	41	36	35	33	32	27	23					
1.00	72	65	57	53	47	45	68	61	54	51	45	43	49	46	41	40	38	37	31	27					
1.25	80	71	65	60	55	52	74	67	62	57	53	50	55	52	48	46	44	42	37	32					
1.50	84	74	71	64	61	56	79	71	67	61	58	54	60	56	53	50	48	46	40	36					
2.00	93	81	80	72	71	65	87	77	76	69	67	62	68	63	61	58	55	53	47	42					
2.50	97	84	86	76	78	70	91	80	82	73	74	67	72	67	66	62	60	57	51	46					
3.00	101	87	91	80	83	74	95	83	86	77	79	71	76	70	71	66	63	60	55	49					
4.00	106	90	98	85	91	80	99	86	92	81	86	77	81	74	76	71	68	65	60	54					
5.00	109	92	102	88	96	83	102	88	96	84	90	80	85	77	80	74	71	68	63	57					
10.00	116	97	112	94	108	91	108	93	105	90	101	88	92	83	90	81	79	75	70	64					

