

東芝照明器具配光データシート

名称	LED照明器具
形名	LEDD87027N-LSX

--	--

効 率	F	0 %
	F	100 %
	F	100 %
	器具 光束	790 lm

保守 率	良	0.67
	中	0.63
	否	0.56

前面	
反射面	

最大取付間隔	
A-A	1.2 H
B-B	1.2 H

備 考	
--------	--

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	469		
10°	474		
20°	459		
30°	394		
40°	321		
50°	201		
60°	89		
70°	24		
80°	7		
90°	0		
100°	0		
110°	0		
120°	0		
130°	0		
140°	0		
150°	0		
160°	0		
170°	0		
180°	0		

反射 率 (%)	天井	80						70						50						30		20		0	
	壁	70		50		30		70		50		30		50		30		30		10		0			
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0		
室指数	固有照明率 (×0.01)																								
0.60	71	65	58	55	50	49	69	64	57	55	50	48	56	54	49	48	48	48	44	42					
0.80	84	76	71	67	63	61	82	75	70	66	63	61	68	65	62	60	61	59	56	54					
1.00	90	81	79	73	71	67	88	80	77	72	70	67	75	71	68	66	67	65	62	60					
1.25	98	87	87	79	79	74	95	85	85	79	78	73	82	77	76	72	74	72	68	66					
1.50	102	90	92	83	84	78	99	89	90	83	83	78	86	81	81	77	78	76	72	71					
2.00	109	95	101	90	94	86	106	94	98	89	92	85	94	87	89	84	86	83	80	78					
2.50	113	98	106	93	99	90	110	96	103	92	97	89	98	91	93	88	90	86	83	82					
3.00	116	100	109	96	104	92	112	98	106	95	101	92	101	93	97	90	93	89	86	85					
4.00	120	102	114	99	110	96	116	101	111	98	107	95	105	96	102	94	97	92	90	88					
5.00	122	103	117	101	113	98	118	102	114	100	110	98	107	98	104	96	99	94	92	90					
10.00	126	106	124	104	121	103	122	104	119	103	117	102	112	101	110	100	104	98	97	95					

