

東芝照明器具配光データシート

名称	LED照明器具
形名	LEDD87922L (K) -LSX

--	--

効 率	F	0 %
	F	100 %
	F	100 %
	器具 光束	370 lm

保守 率	良	0.67
	中	0.63
	否	0.56

前面	
反射面	

最大取付間隔	
A-A	1.2 H
B-B	1.2 H

備 考	
--------	--

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	513		
10°	508		
20°	495		
30°	431		
40°	337		
50°	187		
60°	68		
70°	8		
80°	0		
90°	0		
100°	0		
110°	0		
120°	0		
130°	0		
140°	0		
150°	0		
160°	0		
170°	0		
180°	0		

反射率 (%)	天井	80						70						50						30		20		0	
	壁	70		50		30		70		50		30		50		30		30		10		0			
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0		
室指数	固有照明率 (×0.01)																								
0.60	73	67	61	58	53	52	71	66	60	57	53	52	59	56	52	51	52	51	47	46					
0.80	86	78	75	70	67	64	84	77	74	69	66	64	72	68	65	63	64	63	59	58					
1.00	93	83	82	76	74	70	90	82	80	75	73	70	78	74	72	69	70	68	65	64					
1.25	100	89	89	82	82	77	97	87	88	81	81	76	85	80	79	75	77	75	71	70					
1.50	104	92	94	86	87	81	101	91	93	85	86	81	89	83	84	80	81	79	76	74					
2.00	111	97	103	92	96	88	108	95	100	91	95	87	96	89	91	86	88	85	82	81					
2.50	115	99	107	95	102	92	111	98	105	94	100	91	100	92	96	90	92	88	86	84					
3.00	117	101	111	97	106	94	114	99	108	96	103	94	103	94	99	92	95	91	88	87					
4.00	121	103	116	100	111	98	117	101	112	99	108	97	106	97	103	95	98	94	92	90					
5.00	123	104	118	102	114	100	118	103	115	101	111	99	108	99	105	97	100	95	93	92					
10.00	127	106	124	105	122	104	122	105	120	104	118	103	121	101	111	101	104	99	97	95					

