


東芝照明器具配光データシート

名称	LEDダウンライト
形名	LEDD-09021FL-LS9



効率	F ◡	0 %
	F ◒	100 %
	F ○	100 %
	器具光束	950 lm

保守率	良	0.76
	中	0.72
	否	0.64

前面	カバー (フロスト)
反射面	白色

最大取付間隔	
A-A	1.23 H
B-B	1.23 H

備考

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	453		
10°	446		
20°	429		
30°	383		
40°	309		
50°	216		
60°	112		
70°	28		
80°	2		
90°	0		
100°	0		
110°	0		
120°	0		
130°	0		
140°	0		
150°	0		
160°	0		
170°	0		
180°	0		

反射率 (%)	天井	80						70						50						30		20		0	
	壁	70		50		30		70		50		30		50		30		30		10		0			
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0		
室指数		固有照明率 (×0.01)																							
0.60	69	64	56	53	48	47	67	62	55	53	48	46	54	52	47	46	46	46	42	40					
0.80	82	75	70	65	61	59	80	73	69	65	61	59	67	63	60	58	59	57	54	52					
1.00	89	80	77	71	69	65	87	79	76	71	68	65	73	69	67	64	65	63	60	58					
1.25	97	86	85	78	77	72	94	84	84	77	76	72	80	76	74	71	72	70	66	65					
1.50	101	89	91	82	83	77	98	88	89	82	82	77	85	80	79	76	77	75	71	69					
2.00	109	95	100	89	93	85	105	93	97	88	91	84	93	87	88	83	85	82	79	77					
2.50	113	97	105	93	99	89	109	96	102	92	97	88	97	90	93	87	89	86	83	81					
3.00	116	99	109	95	103	92	112	98	106	94	101	91	100	92	96	90	92	88	86	84					
4.00	120	102	114	99	109	96	116	100	111	98	106	95	105	96	101	94	96	92	90	88					
5.00	122	103	117	101	113	98	118	102	114	99	110	97	107	97	104	96	99	94	92	90					
10.00	126	106	124	104	121	103	122	104	120	103	117	102	112	101	110	100	104	98	97	95					

