

東芝照明器具配光データシート

名称	屋外用LEDブラケット	保守率	良	0.69				
形名	LEDB83906		中	0.67				
			否	0.63				
光源	名称	直管LEDランプ	効率	F	18%	最大取付間隔		
	形名	LDM10SSL/5/4-01		F	51%		A-A	1.59 H
	光束	450 lm × 1		F	69%		B-B	1.59 H
前面	グローブ (乳白)						備考	
反射面	塗装 (白)							

光度 (cd/1000lm)				天井	80						70						50						30						20						0					
θ	φ	A-A	B-B		壁	70		50		30		70		50		30		50		30		30		10		10		10		10		10		0						
0°		96		床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10						
10°		98		室指数	照 明 率 (×0.01)																																			
20°		100		0.60	35	33	25	24	19	18	33	31	24	23	18	17	21	20	16	16	15	14	11	9																
30°		101		0.80	42	38	32	30	25	24	39	36	30	28	24	23	27	25	21	21	19	19	15	12																
40°		99		1.00	48	43	37	35	30	29	45	41	35	33	29	27	31	30	26	25	23	23	19	16																
50°		92		1.25	53	47	42	39	35	33	49	44	40	37	33	32	35	33	30	29	27	26	22	19																
60°		84		1.50	57	50	47	42	40	37	53	47	44	40	38	35	39	36	34	32	30	29	25	22																
70°		72		2.00	62	54	53	48	46	42	58	51	50	45	44	41	44	41	39	37	35	34	29	26																
80°		59		2.50	66	57	58	51	51	46	61	54	54	49	48	44	48	44	43	40	38	37	33	29																
90°		49		3.00	68	58	61	53	55	49	64	56	57	51	52	47	50	46	46	43	41	39	35	31																
100°		45		4.00	72	61	66	57	60	53	67	58	61	54	57	51	54	49	50	46	44	42	38	34																
110°		39		5.00	74	62	69	59	64	56	69	60	64	56	60	53	56	51	53	49	47	44	41	36																
120°		32		10.00	79	66	76	64	73	62	73	63	71	61	68	59	62	56	60	54	52	50	46	42																
130°		25																																						
140°		17																																						
150°		8																																						
160°		1																																						
170°		1																																						
180°		0																																						

