

東芝照明器具配光データシート

名称	屋外用LEDブラケット
形名	LEDB85912

保守率	良	0.69
	中	0.67
	否	0.63

光源	名称	GXランプ
	形名	LDF5L-H-GX5 3/3
	光束	500 lm × 1

効率	F ◡	31%
	F ◣	46%
	F ○	77%
	器具光束	385 lm

最大取付間隔	
A-A	1.48 H
B-B	1.48 H

前面	グローブ (乳白)
反射面	

備考	
----	--

θ	φ	光度 (cd/1000lm)		
		A-A	B-B	C-C
0°		85		
10°		83		
20°		82		
30°		82		
40°		81		
50°		78		
60°		74		
70°		69		
80°		62		
90°		60		
100°		58		
110°		55		
120°		52		
130°		47		
140°		43		
150°		37		
160°		32		
170°		29		
180°		0		

反射率 (%)	天井		80				70				50				30		20		0	
	壁	床	70	50	30	70	50	30	50	30	50	30	30	10	30	10	10	0		
室指数	照明率 (×0.01)																			
0.60	38	35	27	26	20	20	35	33	25	24	19	19	22	21	16	16	14	14	10	7
0.80	45	41	34	32	27	25	42	38	31	30	25	24	27	26	21	21	18	18	14	10
1.00	52	46	40	37	32	31	47	43	37	35	30	29	32	30	26	25	22	21	17	13
1.25	57	50	46	42	38	35	52	47	42	39	35	33	36	34	30	29	26	25	20	16
1.50	61	53	50	45	42	39	56	50	46	42	39	37	39	37	34	32	29	28	23	18
2.00	67	58	57	51	49	45	61	54	53	48	46	42	44	41	39	37	33	32	27	22
2.50	71	61	62	55	55	49	64	57	57	51	51	46	48	44	43	41	36	35	30	24
3.00	73	63	65	57	59	52	67	59	60	54	54	49	51	47	46	43	39	37	32	26
4.00	77	66	70	61	64	57	71	61	65	57	60	53	54	50	51	47	42	40	35	29
5.00	80	67	74	63	68	60	73	63	68	59	63	56	57	52	54	49	45	43	38	31
10.00	85	71	81	69	78	66	78	67	75	64	72	62	63	57	61	55	51	48	43	36

