


東芝照明器具配光データシート

名称	LEDダウンライト
形名	LEDD-60021MW-LD9



効率	F ◡	0 %
	F ◣	100 %
	F ○	100 %
器具光束		5200 lm

保守率	良	0.76
	中	0.72
	否	0.64

前面	梨地処理
反射面	下面開放

最大取付間隔	
A-A	1.13 H
B-B	1.13 H

備考

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	695		
10°	670		
20°	629		
30°	535		
40°	337		
50°	85		
60°	18		
70°	1		
80°	0		
90°	0		
100°	0		
110°	0		
120°	0		
130°	0		
140°	0		
150°	0		
160°	0		
170°	0		
180°	0		

反射率 (%)	天井	80						70						50						30		20		0	
	壁	70		50		30		70		50		30		50		30		30		10		0			
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0		
室指数		固有照明率 (×0.01)																							
0.60	81	74	70	66	63	61	79	73	69	66	63	61	68	65	62	61	62	60	58	56					
0.80	93	85	83	78	77	74	92	84	82	78	76	73	80	77	75	73	74	72	70	68					
1.00	99	89	89	83	83	78	97	88	88	82	82	78	85	81	80	77	79	77	74	73					
1.25	105	93	95	88	89	83	102	92	94	87	88	83	91	86	86	82	84	81	79	78					
1.50	108	95	100	91	94	87	105	94	98	90	92	87	95	89	90	86	88	85	82	81					
2.00	114	99	107	95	101	92	111	98	104	95	99	92	100	93	96	91	93	90	87	86					
2.50	117	101	111	98	105	95	114	100	108	97	103	94	103	95	99	93	96	92	90	88					
3.00	119	102	114	99	109	97	116	101	111	99	106	96	105	97	102	95	98	94	92	90					
4.00	122	104	117	102	113	100	118	103	114	101	111	99	108	99	105	97	101	96	94	92					
5.00	124	105	120	103	116	101	120	103	116	102	113	100	110	100	107	99	102	97	95	94					
10.00	127	106	125	105	123	104	123	105	121	104	119	103	113	102	112	101	105	100	98	96					

