

東芝照明器具配光データシート

名称	LED高天井用照明器具
形名	LEDJ-40045N-DJ2

効 率	F ◡	0 %
	F ◣	100 %
	F ○	100 %
	器具 光束	43200 lm

保 守 率	良	0.88
	中	0.86
	否	0.81

前面	
反射面	レンズ(広角)

最大取付間隔	
A-A	1.23 H
B-B	1.23 H

--	--

備 考	初期照度補正機能付きです。光束・照度は記載値の約0.86倍です。
--------	----------------------------------

光度(cd/1000lm)			
θ \ φ	A-A	B-B	C-C
0°	491	491	491
10°	472	482	475
20°	459	459	459
30°	420	420	420
40°	329	329	329
50°	168	185	171
60°	88	86	89
70°	29	32	29
80°	3	3	3
90°	0	0	0
100°	0	0	0
110°	0	0	0
120°	0	0	0
130°	0	0	0
140°	0	0	0
150°	1	1	1
160°	1	1	1
170°	1	1	1
180°	1	1	1

反 射 率 (%)	天井	80						70						50						30		20		0
	壁	70		50		30		70		50		30		50		30		30		10		0		
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0	
	室指数	固有照明率(×0.01)																						
	0.60	71	66	59	56	51	50	70	65	58	55	51	49	57	54	50	49	49	48	45	43			
	0.80	84	77	72	68	64	62	82	75	71	67	64	61	69	66	63	61	62	60	57	55			
	1.00	91	82	79	74	71	68	89	80	78	73	71	67	75	72	69	67	68	66	62	61			
	1.25	98	87	87	80	79	74	95	86	85	79	78	74	82	78	76	73	74	72	69	67			
	1.50	103	90	92	84	85	79	100	89	90	83	84	78	87	81	81	77	79	76	73	71			
	2.00	110	95	101	90	94	86	106	94	99	89	93	85	94	88	89	84	86	83	80	78			
	2.50	114	98	106	94	100	90	110	97	103	93	98	89	98	91	94	88	90	87	84	82			
	3.00	116	100	110	96	104	93	113	98	107	95	102	92	101	93	97	91	93	89	87	85			
	4.00	120	102	115	99	110	97	116	101	111	98	107	96	105	96	102	94	97	92	90	88			
	5.00	122	103	117	101	113	99	118	102	114	100	110	98	107	98	104	96	99	94	92	90			
	10.00	126	106	124	104	121	103	122	104	120	103	117	102	112	101	110	100	104	98	97	95			

