

東芝照明器具配光データシート

名称	LED高天井用照明器具
形名	LEDJ-20028N-DJ2

効 率	F	0 %
	F	100 %
	F	100 %
器具 光束		21600 lm

保 守 率	良	0.88
	中	0.86
	否	0.81

前面	
反射面	レンズ(中角)

最大取付間隔	
A-A	0.87 H
B-B	0.91 H

初期照度補正機能付きです。光束・照度は記載値の約0.86倍です。

光度(cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	1257	1257	1257
10°	1238	1290	1259
20°	1083	1079	1080
30°	432	483	364
40°	54	46	46
50°	30	28	29
60°	23	21	22
70°	16	15	15
80°	4	4	4
90°	0	0	0
100°	0	0	0
110°	0	0	0
120°	0	0	0
130°	0	0	0
140°	0	0	0
150°	1	1	1
160°	1	1	1
170°	2	2	2
180°	3	3	3

反射率 (%)	天井		80				70				50				30		20		0	
	壁	床	70	50	30	70	50	30	70	50	30	50	30	30	10	10	10	0		
室指数	固有照明率(×0.01)																			
0.60	95	87	86	82	81	79	93	86	86	82	81	79	84	81	80	78	79	78	76	75
0.80	105	95	97	91	92	88	103	94	96	91	92	88	94	90	90	88	89	87	86	85
1.00	107	96	99	92	94	90	105	95	98	92	93	89	96	91	92	89	90	88	86	85
1.25	110	98	102	94	97	91	108	97	101	93	96	91	98	92	94	90	92	89	87	86
1.50	113	99	105	96	100	93	110	98	104	95	99	93	100	94	96	92	94	91	89	88
2.00	116	101	110	98	105	96	113	100	108	97	103	95	103	96	100	94	97	93	91	90
2.50	119	102	113	100	108	98	115	101	110	99	106	97	105	97	102	96	98	94	93	91
3.00	120	103	115	101	111	99	117	102	112	100	109	98	107	98	104	97	100	96	94	92
4.00	123	105	119	103	115	101	119	104	116	102	113	101	110	100	107	99	102	98	96	94
5.00	125	106	122	104	118	103	121	105	118	103	115	102	111	101	109	101	104	99	98	96
10.00	129	108	127	107	126	107	124	106	123	106	122	106	115	104	114	104	108	102	101	99

