

東芝照明器具配光データシート

名称	LED高天井用照明器具					
形名	LEDJ-10020N-DJ2					
効 率	F	0 %	保 守 率	良	0.88	備 考
	F	100 %		中	0.86	
	F	100 %		否	0.81	
	器具 光束	17000 lm	最大取付間隔		初期照度補正機能付きです。光束・照度は記載値の約0.86倍です。	
前 面		A-A	1.23 H			
反射面	レンズ (広角)	B-B	1.23 H			

光度 (cd/1000lm)				反射率 (%)	天井		80				70				50				30		20		0		
$\theta \backslash \phi$	A-A	B-B	C-C		壁	70	50	30	70	50	30	70	50	30	50	30	30	10	10	10	0				
0°	491	491	491	室指数	固有照明率 (×0.01)																				
10°	472	482	475		0.60	71	66	59	56	51	50	70	65	58	55	51	49	57	54	50	49	49	48	45	43
20°	459	459	459		0.80	84	77	72	68	64	62	82	75	71	67	64	61	69	66	63	61	62	60	57	55
30°	420	420	420		1.00	91	82	79	74	71	68	89	80	78	73	71	67	75	72	69	67	68	66	62	61
40°	329	329	329		1.25	98	87	87	80	79	74	95	86	85	79	78	74	82	78	76	73	74	72	69	67
50°	168	185	171		1.50	103	90	92	84	85	79	100	89	90	83	84	78	87	81	81	77	79	76	73	71
60°	88	86	89		2.00	110	95	101	90	94	86	106	94	99	89	93	85	94	88	89	84	86	83	80	78
70°	29	32	29		2.50	114	98	106	94	100	90	110	97	103	93	98	89	98	91	94	88	90	87	84	82
80°	3	3	3		3.00	116	100	110	96	104	93	113	98	107	95	102	92	101	93	97	91	93	89	87	85
90°	0	0	0		4.00	120	102	115	99	110	97	116	101	111	98	107	96	105	96	102	94	97	92	90	88
100°	0	0	0		5.00	122	103	117	101	113	99	118	102	114	100	110	98	107	98	104	96	99	94	92	90
110°	0	0	0		10.00	126	106	124	104	121	103	122	104	120	103	117	102	112	101	110	100	104	98	97	95
120°	0	0	0																						
130°	0	0	0																						
140°	0	0	0																						
150°	1	1	1																						
160°	1	1	1																						
170°	1	1	1																						
180°	1	1	1																						

