

# 東芝照明器具配光データシート

名称	LED照明器具
形名	LEDC88028-8G

保守率	良	0.67
	中	0.63
	否	0.56

最大取付間隔	
A-A	1.48 H
B-B	1.48 H

光源	名称	LEDランプ
	形名	LDA8L-G/60W
	光束	810 lm × 8

効率	F 	14%
	F 	54%
	F 	68%
	器具光束	4420 lm

備考	
----	--

前面	
反射面	

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	110		
10°	115		
20°	121		
30°	113		
40°	99		
50°	87		
60°	80		
70°	75		
80°	72		
90°	66		
100°	60		
110°	30		
120°	10		
130°	0		
140°	0		
150°	0		
160°	0		
170°	0		
180°	0		

反射率 (%)	天井	80				70				50				30		20		0		
	壁	70		50		30		70		50		30		50		30		10	0	
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0	
室指数	照 明 率 (×0.01)																			
0.60	36	34	26	25	20	20	34	32	25	24	19	19	23	22	18	18	17	16	13	11
0.80	44	40	33	31	26	25	41	38	32	30	25	24	29	27	23	23	22	21	17	15
1.00	48	43	38	35	31	29	45	41	36	34	29	28	33	31	27	26	25	24	20	18
1.25	53	47	43	39	36	34	50	45	41	38	34	32	37	35	31	30	29	28	24	21
1.50	57	50	47	42	40	37	53	47	44	41	38	35	40	37	35	33	31	30	26	23
2.00	62	54	53	48	46	42	58	51	50	46	44	41	45	42	40	38	36	35	31	28
2.50	65	56	57	51	51	46	61	54	54	49	48	44	48	45	44	41	39	38	34	30
3.00	68	58	61	53	54	48	64	56	57	51	52	47	51	47	47	43	42	40	36	33
4.00	71	61	65	56	60	52	67	58	61	54	56	50	55	50	51	47	46	43	40	36
5.00	74	62	68	58	63	55	69	60	64	56	60	53	57	52	54	49	48	46	42	38
10.00	79	66	75	63	72	61	74	63	71	61	68	59	63	57	60	55	54	51	48	44

