

東芝照明器具配光データシート

名称	東芝LED照明器具
形名	LEDB85906Y (W)N

保守率	良	0.69
	中	0.67
	否	0.63

最大取付間隔	
A-A	1.2 H
B-B	1.2 H

光源	名称	LED1ユニットフラット形
	形名	LDF7L-H-GX5 3/3
	光束	510 lm × 1

効率	F	1%
	F	50%
	F	51%
	器具光束	260 lm

備考	
----	--

前面	
反射面	

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	169	169	169
10°	167	171	174
20°	164	165	163
30°	133	135	132
40°	113	106	115
50°	98	94	89
60°	72	82	70
70°	58	52	53
80°	41	34	37
90°	15	20	20
100°	0	0	0
110°	0	0	0
120°	0	0	0
130°	0	0	0
140°	0	0	0
150°	0	0	0
160°	0	0	0
170°	0	0	0
180°	0	0	0

反射率 (%)	天井	80						70						50						30		20		0	
	壁	70	50	30	70	50	30	70	50	30	50	30	50	30	30	10	0	10	0						
室指数	照明率 (×0.01)																								
0.60	31	29	24	23	19	19	30	28	23	22	19	19	22	22	19	18	18	18	16	15					
0.80	37	34	30	28	25	24	36	33	29	27	25	24	28	27	24	23	23	23	20	19					
1.00	41	37	33	31	28	27	39	36	33	30	28	27	31	29	27	26	26	26	23	22					
1.25	45	40	37	34	32	30	43	39	36	34	32	30	35	33	31	29	30	29	26	25					
1.50	47	41	40	37	35	33	45	40	39	36	35	32	37	35	33	32	32	31	29	27					
2.00	51	45	45	40	41	37	49	44	44	40	40	37	41	39	38	36	36	35	33	31					
2.50	54	46	48	43	44	40	52	45	47	42	43	39	44	41	41	38	39	37	35	34					
3.00	56	48	51	44	47	42	53	47	49	44	45	41	46	42	43	40	41	39	37	36					
4.00	58	49	54	47	51	44	56	48	52	46	49	44	49	45	46	43	44	42	40	39					
5.00	60	50	56	48	53	46	57	49	54	47	51	46	51	46	48	44	46	43	42	40					
10.00	63	53	61	51	59	50	60	52	59	51	57	49	54	49	53	48	50	47	46	44					

