

東芝照明器具配光データシート

名称	東芝LED照明器具
形名	LEDB88910YN

保守率	良	0.69
	中	0.67
	否	0.63

最大取付間隔	
A-A	1.4 H
B-B	1.4 H

光源	名称	LED電球
	形名	LDA5L-G-E17 /S/40W
	光束	380 lm × 1

効率	F ◡	26%
	F ◣	59%
	F ○	85%
	器具光束	320 lm

最大取付間隔	
A-A	1.4 H
B-B	1.4 H

備考

前面	
反射面	

光度 (cd/1000lm)			
θ \ φ	A-A	B-B	C-C
0°	120		
10°	119		
20°	117		
30°	113		
40°	107		
50°	100		
60°	93		
70°	85		
80°	77		
90°	69		
100°	60		
110°	52		
120°	43		
130°	35		
140°	28		
150°	11		
160°	9		
170°	6		
180°	0		

反射率 (%)	天井	80						70						50						30		20		0	
	壁	70	50	30	70	50	30	70	50	30	50	30	50	30	30	10	0								
床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0								
室指数	照 明 率 (×0.01)																								
0.60	44	40	32	30	24	23	41	38	30	28	23	22	26	25	21	20	18	18	14	11					
0.80	53	48	40	37	32	30	49	45	38	35	30	29	33	32	27	26	24	23	19	16					
1.00	58	52	46	42	37	35	54	49	43	40	35	33	38	36	31	30	28	27	22	19					
1.25	65	57	52	48	43	41	60	54	49	45	41	39	43	40	37	35	32	31	26	22					
1.50	69	60	57	51	48	45	64	57	53	49	45	42	47	44	40	38	36	34	29	25					
2.00	75	66	65	58	56	51	70	62	61	55	53	49	53	49	47	44	41	40	34	30					
2.50	80	69	70	62	62	56	74	65	65	58	58	53	57	52	51	48	45	43	38	33					
3.00	83	71	74	65	66	59	77	67	69	61	62	56	60	55	55	51	48	46	41	35					
4.00	87	74	79	69	73	64	81	70	74	65	68	61	64	59	60	55	52	50	45	39					
5.00	90	76	83	71	77	67	83	72	77	68	72	64	67	61	63	58	55	52	47	41					
10.00	96	80	92	77	88	75	89	76	85	74	82	71	74	67	71	65	62	58	54	48					

