

# 東芝照明器具配光データシート

名称	東芝LED照明器具
形名	LEDG85906Y (K) N

保守率	良	0.69
	中	0.67
	否	0.63

最大取付間隔	
A-A	1.2 H
B-B	1.2 H

光源	名称	LED1ユニットフラット形
	形名	LDF7L-H-GX5 3/3
	光束	510 lm × 1

効率	F	1%
	F	45%
	F	46%
	器具光束	230 lm

最大取付間隔	
A-A	1.2 H
B-B	1.2 H

備考
----

前面	
反射面	

θ \ φ	光度 (cd/1000lm)		
	A-A	B-B	C-C
0°	145	145	145
10°	137	136	141
20°	136	139	143
30°	119	123	129
40°	101	89	111
50°	93	86	83
60°	68	76	67
70°	55	53	51
80°	28	21	28
90°	13	11	9
100°	0	0	0
110°	0	0	0
120°	0	0	0
130°	0	0	0
140°	0	0	0
150°	0	0	0
160°	0	0	0
170°	0	0	0
180°	0	0	0

反射率 (%)	天井	80						70						50						30		20		0	
	壁	70	50	30	70	50	30	70	50	30	50	30	50	30	30	10	0	10	0						
床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30						
室指数	照明率 (×0.01)																								
0.60	27	25	21	20	17	16	27	25	20	19	17	16	20	19	16	16	16	14	13						
0.80	33	30	26	25	22	21	32	29	26	24	22	21	25	23	21	20	21	20	18	17					
1.00	36	32	30	27	25	24	35	32	29	27	25	24	28	26	24	23	23	23	21	20					
1.25	40	35	33	31	29	27	38	34	32	30	28	27	31	29	27	26	27	26	23	22					
1.50	42	37	36	33	32	29	40	36	35	32	31	29	33	31	30	28	29	28	26	25					
2.00	46	40	40	36	36	33	44	39	39	36	36	33	37	35	34	32	33	31	29	28					
2.50	48	41	43	38	39	36	46	40	42	38	38	35	40	37	37	34	35	34	32	31					
3.00	50	43	45	40	42	37	48	42	44	39	41	37	41	38	39	36	37	35	34	33					
4.00	52	44	48	42	45	40	50	43	47	41	44	39	44	40	42	38	40	38	36	35					
5.00	53	45	50	43	48	41	51	44	48	42	46	41	45	41	44	40	41	39	38	37					
10.00	56	47	54	46	53	45	54	46	52	45	51	44	49	44	48	43	45	42	41	40					

