

東芝照明器具配光データシート

名称	東芝LED照明器具
形名	LEDG85906Y (S) N

保守率	良	0.69
	中	0.67
	否	0.63

光源	名称	LED1ユニットフラット形
	形名	LDF7L-H-GX5 3/3
	光束	510 lm × 1

効率	F ◡	5%
	F ◣	55%
	F ○	60%
	器具光束	305 lm

最大取付間隔	
A-A	1.2 H
B-B	1.2 H

前面	
反射面	

備考	最大取付間隔	
	A-A	1.2 H
	B-B	1.2 H

θ \ φ	光度 (cd/1000lm)		
	A-A	B-B	C-C
0°	188		
10°	184		
20°	171		
30°	147		
40°	123		
50°	105		
60°	83		
70°	59		
80°	37		
90°	20		
100°	17		
110°	16		
120°	0		
130°	0		
140°	0		
150°	0		
160°	0		
170°	0		
180°	0		

反射率 (%)	天井	80						70						50						30		20		0				
	壁	70	50	30	70	50	30	70	50	30	50	30	50	30	30	10	0	30	10	0	30	10	0	30	10	0	30	10
室指数	照明率 (×0.01)																											
0.60	36	33	27	26	22	21	34	32	26	25	22	21	25	24	21	20	20	20	17	16								
0.80	42	39	34	32	28	27	41	37	33	31	28	27	31	30	27	26	26	25	22	21								
1.00	47	42	38	35	32	31	45	41	37	35	32	30	35	33	30	29	29	28	25	24								
1.25	51	45	43	39	37	35	49	44	42	38	36	34	39	37	35	33	33	32	29	27								
1.50	54	48	46	42	41	38	52	46	45	41	40	37	42	39	38	36	36	35	32	30								
2.00	59	51	52	46	47	43	56	50	50	45	45	42	47	43	43	40	41	39	36	34								
2.50	62	53	56	49	51	46	59	52	53	48	49	45	50	46	46	43	43	42	39	37								
3.00	64	55	58	51	54	48	61	53	56	50	52	47	52	48	49	45	46	44	41	39								
4.00	67	57	62	54	58	51	64	55	60	53	56	50	55	50	52	48	49	47	44	42								
5.00	68	58	64	55	61	53	65	56	62	54	59	52	57	52	55	50	51	48	46	44								
10.00	72	60	70	59	68	58	69	59	67	58	65	56	61	55	60	54	56	52	51	49								

