

東芝照明器具配光データシート

名称	東芝LED照明器具
形名	LEDS88900Y (K) N

保守率	良	0.69
	中	0.67
	否	0.63

最大取付間隔	
A-A	0.87H
B-B	0.87H

光源	名称	LED電球
	形名	LDA7L-H
	光束	500 lm × 1

効率	F	0%
	F	37%
	F	37%
	器具光束	185 lm

備考	
----	--

前面	
反射面	

0°	269	25°	
1°		30°	117
2°		35°	
3°		40°	75
4°		45°	
5°		50°	61
6°		55°	
7°		60°	37
8°		65°	
9°		70°	16
10°	266	75°	
11°		80°	10
12°		85°	
13°		90°	4
14°			
15°			
16°			
17°			
18°			
19°			
20°	205		

反射率 (%)	天井	80				70				50				30		20		0		
	壁	70	50	30	70	50	30	50	30	50	30	30	10	10	0					
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0			
室指数	照明率 (×0.01)																			
0.60	25	23	20	19	17	17	25	23	20	19	17	17	20	19	17	17	16	15	14	
0.80	29	26	24	23	21	20	28	26	24	22	21	20	23	22	21	20	20	18	18	
1.00	32	29	28	26	24	23	31	28	27	25	24	23	26	25	24	23	23	22	21	20
1.25	35	31	30	28	27	25	34	30	30	27	27	25	28	27	26	25	25	23	22	
1.50	36	32	32	29	29	27	35	32	32	29	29	27	30	28	28	27	27	26	25	24
2.00	39	34	35	32	33	30	38	33	35	31	32	29	33	31	31	29	30	29	27	27
2.50	41	35	37	33	35	31	39	34	36	33	34	31	34	32	33	31	31	30	29	28
3.00	42	36	39	34	37	33	40	35	38	34	36	32	36	33	34	32	33	31	30	29
4.00	43	37	41	35	39	34	42	36	40	35	38	34	37	34	36	33	34	33	32	31
5.00	44	37	42	36	40	35	42	37	41	36	39	35	38	35	37	34	35	33	33	32
10.00	46	38	45	38	44	37	44	38	43	37	43	37	41	37	40	36	38	35	35	34

