

東芝照明器具配光データシート

名称	東芝LED照明器具
形名	LEDS88900Y (S) N

保守率	良	0.69
	中	0.67
	否	0.63

最大取付間隔	
A-A	0.9 H
B-B	0.9 H

光源	名称	LED電球
	形名	LDA7L-H
	光束	500 lm × 1

効率	F	0%
	F	37%
	F	37%
	器具光束	185 lm

備考	
----	--

前面	
反射面	

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	269		
10°	266		
20°	205		
30°	117		
40°	75		
50°	61		
60°	37		
70°	16		
80°	10		
90°	4		
100°	0		
110°	0		
120°	0		
130°	0		
140°	0		
150°	0		
160°	0		
170°	0		
180°	0		

反射率 (%)	天井	80						70						50						30		20		0	
	壁	70		50		30		70		50		30		50		30		30		10		0			
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0		
室指数	照明率 (×0.01)																								
0.60	27	25	22	21	20	19	26	24	22	21	20	19	22	21	19	19	19	19	17	17					
0.80	31	28	27	25	24	23	31	28	27	25	24	23	26	25	23	23	23	23	21	21					
1.00	33	30	29	27	26	25	32	29	29	27	26	25	28	26	25	24	25	24	23	22					
1.25	36	32	32	29	29	27	35	31	31	29	28	27	30	28	27	26	27	26	25	24					
1.50	37	33	33	30	30	28	36	32	33	30	30	28	31	29	29	28	28	27	26	25					
2.00	40	34	36	32	34	31	38	34	35	32	33	30	34	31	32	30	31	29	28	28					
2.50	41	35	38	34	36	32	40	35	37	33	35	32	35	32	33	31	32	31	30	29					
3.00	42	36	39	34	37	33	41	35	38	34	36	33	36	33	35	32	33	32	31	30					
4.00	43	37	41	36	39	35	42	36	40	35	38	34	38	34	36	34	35	33	32	31					
5.00	44	37	42	36	41	35	43	37	41	36	40	35	39	35	38	34	36	34	33	32					
10.00	46	39	45	38	44	38	44	38	44	38	43	37	41	37	40	36	38	36	35	34					

