

東芝照明器具配光データシート

名称	LED照明器具
形名	LEDH81773-LC



効 率	F	16%
	F	84%
	F	100%
	器具 光束	3800 lm

保守 率	良	0.63
	中	0.60
	否	0.56

前面	カバー (乳白)
反射面	塗装 (白)

最大取付間隔	
A-A	1.3 H
B-B	1.3 H

備考	
----	--

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	225	225	225
10°	226	222	225
20°	220	214	219
30°	206	198	205
40°	184	175	184
50°	160	151	158
60°	135	129	130
70°	108	105	101
80°	78	76	72
90°	45	43	45
100°	37	34	39
110°	31	29	34
120°	26	24	29
130°	20	19	24
140°	15	14	18
150°	11	10	13
160°	7	6	8
170°	3	3	3
180°	1	1	1

反射率 (%)	天井	80						70						50						30		20		0							
	壁	70	50	30	70	50	30	70	50	30	50	30	50	30	30	10	0	30	10	0	30	10	0	30	10	0	30	10	0		
床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30		
室指数	固有照明率 (×0.01)																														
0.60	57	52	42	40	33	32	54	50	40	39	32	31	38	36	30	30	29	28	23	21											
0.80	68	61	53	49	43	41	64	59	51	48	42	40	47	45	39	38	37	36	31	28											
1.00	75	67	60	56	50	47	71	64	58	54	48	46	53	50	45	44	43	41	36	33											
1.25	82	73	68	62	58	54	78	70	65	60	56	53	60	56	52	50	49	47	42	38											
1.50	87	77	74	67	64	59	82	74	70	65	61	57	65	60	57	54	53	51	46	42											
2.00	95	83	83	74	74	67	90	80	80	72	71	66	73	67	66	62	61	59	53	49											
2.50	100	86	89	79	81	73	95	83	85	76	77	71	77	72	71	67	66	63	58	54											
3.00	104	89	94	82	86	77	98	86	90	80	82	75	81	75	76	70	69	66	61	57											
4.00	109	93	101	87	94	82	103	89	96	84	89	80	87	79	82	75	75	71	67	62											
5.00	112	95	105	90	99	86	106	91	100	87	94	83	90	82	86	79	78	74	70	65											
10.00	119	99	114	96	111	94	112	96	108	94	105	91	98	88	95	86	86	81	77	73											

