

東芝照明器具配光データシート

名称	LED照明器具
形名	LEDH82772-LC



効 率	F $\frac{1}{2}$	14%
	F $\frac{3}{4}$	86%
	F \bigcirc	100%
	器具 光束	4900 lm

保守 率	良	0.63
	中	0.60
	否	0.56

前面	カバー (乳白)
反射面	塗装 (白)

最大取付間隔	
A-A	1.3 H
B-B	1.3 H

備考	
----	--

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	263	263	263
10°	261	259	260
20°	250	247	249
30°	230	226	228
40°	201	197	200
50°	169	164	166
60°	133	129	130
70°	98	95	94
80°	65	62	61
90°	38	38	37
100°	34	34	35
110°	29	29	31
120°	24	24	25
130°	17	17	17
140°	12	12	10
150°	6	6	3
160°	1	1	1
170°	1	1	1
180°	1	1	1

反射率 (%)	天井	80						70						50						30		20		0
	壁	70	50	30	70	50	30	70	50	30	50	30	50	30	30	10	0							
床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0							
室指数	固有照明率 (×0.01)																							
0.60	58	54	44	42	35	34	56	52	43	41	35	34	40	38	33	32	31	31	26	24				
0.80	70	63	55	52	46	44	67	61	53	50	45	43	50	48	42	41	40	39	34	32				
1.00	77	69	62	58	53	50	73	66	60	56	51	49	56	53	49	47	46	45	40	37				
1.25	84	75	71	65	61	57	80	72	68	63	59	56	63	59	55	53	52	51	45	42				
1.50	89	79	76	69	67	62	85	76	73	67	64	60	68	63	60	58	57	55	50	46				
2.00	97	85	86	77	77	70	93	82	82	75	74	68	76	70	69	65	64	62	57	53				
2.50	102	88	92	81	83	75	97	85	88	79	80	73	81	74	74	70	69	66	62	58				
3.00	106	91	96	85	89	79	100	88	92	82	85	77	84	78	79	73	73	70	65	61				
4.00	111	94	103	89	96	84	105	91	98	87	92	82	89	82	85	78	78	74	70	66				
5.00	113	96	107	92	101	88	108	93	102	89	97	86	93	84	89	81	81	77	73	69				
10.00	120	100	116	98	112	95	114	97	110	95	107	93	100	90	97	88	89	84	81	76				

