

東芝照明器具配光データシート

名称	LED照明器具
形名	LEDH84772-LC



効 率	F	14 %
	F	86 %
	F	100 %
	器具 光束	4450 lm

保守 率	良	0.63
	中	0.60
	否	0.56

前面	カバー (乳白)
反射面	塗装 (白)

最大取付間隔	
A-A	1.3 H
B-B	1.3 H

備考	
----	--

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	259	259	259
10°	257	256	256
20°	247	244	246
30°	228	224	226
40°	201	194	199
50°	169	162	166
60°	135	127	130
70°	101	93	95
80°	68	61	63
90°	40	36	38
100°	35	32	35
110°	30	28	31
120°	25	23	26
130°	20	17	18
140°	13	11	10
150°	7	5	3
160°	2	1	1
170°	1	1	1
180°	1	1	1

反射率 (%)	天井	80						70						50						30		20		0	
	壁	70		50		30		70		50		30		50		30		30		10		0			
床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0	0	
室指数	固有照明率 (×0.01)																								
0.60	58	54	44	42	35	34	56	52	42	40	34	33	40	38	33	32	31	31	26	24					
0.80	70	63	55	52	46	44	66	61	53	50	44	43	50	47	42	41	40	39	34	31					
1.00	77	69	62	58	52	50	73	66	60	56	51	49	56	53	48	47	46	44	39	36					
1.25	84	75	70	64	60	57	80	72	68	63	59	55	63	59	55	53	52	50	45	42					
1.50	89	78	76	69	66	62	85	76	73	67	64	60	67	63	60	57	56	55	49	46					
2.00	97	85	86	77	77	70	92	82	82	74	74	68	75	70	69	65	64	62	57	53					
2.50	102	88	92	81	83	75	97	85	88	79	80	73	80	74	74	70	69	66	61	57					
3.00	106	91	96	84	88	79	100	88	92	82	85	77	84	77	79	73	73	70	65	61					
4.00	110	94	103	89	96	84	105	91	98	86	92	82	89	82	85	78	78	74	70	66					
5.00	113	96	107	92	101	88	107	93	102	89	96	85	92	84	88	81	81	77	73	69					
10.00	120	100	116	98	112	95	114	97	110	95	107	93	100	90	97	88	89	84	80	76					

