

# 東芝照明器具配光データシート

名称	LED照明器具
形名	LEDH84773-LC



効 率	F	16%
	F	84%
	F	100%
	器具 光束	4300 lm

保守 率	良	0.63
	中	0.60
	否	0.56

前面	カバー (乳白)
反射面	塗装 (白)

最大取付間隔	
A-A	1.3 H
B-B	1.3 H

備考	
----	--

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	222	222	222
10°	222	221	222
20°	217	214	217
30°	203	198	205
40°	182	176	184
50°	159	152	158
60°	135	128	130
70°	110	104	102
80°	81	74	73
90°	48	46	45
100°	37	33	38
110°	31	28	34
120°	26	23	29
130°	22	18	24
140°	16	14	18
150°	11	10	13
160°	7	6	8
170°	4	3	4
180°	1	1	1

反射率 (%)	天井	80			70			50			30		20	0						
	壁	70	50	30	70	50	30	50	30	30	30	10	10	0						
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0				
室指数	固有照明率 (×0.01)																			
0.60	56	52	42	40	33	32	54	50	40	38	32	31	38	36	30	30	29	28	23	21
0.80	68	61	53	49	43	41	64	59	51	48	42	40	47	45	39	38	37	36	31	28
1.00	74	67	60	55	50	47	71	64	57	54	48	46	53	50	45	44	42	41	36	33
1.25	82	73	68	62	58	54	78	70	65	60	56	53	60	56	52	50	49	47	42	38
1.50	87	77	73	67	64	59	82	74	70	65	61	57	64	60	57	54	53	51	46	42
2.00	95	83	83	74	74	67	90	80	79	72	71	65	72	67	66	62	61	58	53	49
2.50	100	86	89	79	80	72	95	83	85	76	77	70	77	71	71	67	65	63	58	53
3.00	104	89	94	82	86	77	98	86	90	80	82	74	81	75	75	70	69	66	61	57
4.00	109	92	101	87	94	82	103	89	96	84	89	80	86	79	82	75	75	71	66	62
5.00	112	95	105	90	99	86	106	91	99	87	94	83	90	82	86	79	78	74	70	65
10.00	119	99	114	96	110	94	112	96	108	94	105	91	97	88	95	86	86	81	77	73

