

# 東芝照明器具配光データシート

名称	LED照明器具
形名	LEDG88075Y

保守率	良	0.63
	中	0.60
	否	0.56

--	--

光源	名称	LEDランプ
	形名	LDA8L-G/60W
	光束	810 lm × 1

効率	F	25%
	F	60%
	F	85%
	器具光束	690 lm

最大取付間隔	
A-A	1.65 H
B-B	1.65 H

備考	
----	--

前面	
反射面	

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	127		
10°	130		
20°	139		
30°	146		
40°	137		
50°	115		
60°	89		
70°	66		
80°	57		
90°	54		
100°	53		
110°	50		
120°	45		
130°	39		
140°	32		
150°	23		
160°	12		
170°	2		
180°	0		

反射率 (%)	天井	80						70						50						30		20		0	
	壁	70		50		30		70		50		30		50		30		30		10		0			
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10		
室指数	照明率 (×0.01)																								
0.60	46	42	34	32	26	26	43	40	32	31	25	25	29	28	23	22	21	20	16	14					
0.80	55	50	43	40	35	33	52	47	40	38	33	32	36	34	30	29	27	27	22	19					
1.00	61	55	49	45	40	38	57	52	46	43	39	37	41	39	35	34	31	31	26	22					
1.25	67	60	55	51	47	44	63	56	52	48	45	42	46	44	40	39	36	35	30	26					
1.50	71	63	60	55	52	48	67	59	57	52	49	46	50	47	44	42	39	38	33	29					
2.00	78	68	68	61	60	55	73	64	64	58	57	53	56	52	51	48	45	44	39	34					
2.50	82	71	73	65	66	59	76	67	69	62	62	57	60	56	55	52	49	47	42	37					
3.00	85	73	77	67	70	63	79	69	72	64	66	60	63	58	59	54	52	49	44	39					
4.00	89	76	82	71	76	67	83	72	77	68	72	64	67	61	63	58	56	53	48	43					
5.00	92	78	86	74	80	70	85	74	80	70	75	67	70	64	66	61	58	55	51	45					
10.00	97	81	94	79	90	77	90	78	87	75	84	73	76	68	74	67	64	61	56	50					

