

東芝照明器具配光データシート

名称	LED照明器具
形名	LEDD-21311WV-LD9



効 率	F	0 %
	F	100 %
	F	100 %
	器具 光束	1350 lm

保守 率	良	0.81
	中	0.77
	否	0.68

前面	下面開放
反射面	鏡面処理

最大取付間隔	
A-A	0.9 H
B-B	0.9 H

備考	
----	--

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	1184		
10°	1213		
20°	977		
30°	462		
40°	138		
50°	27		
60°	3		
70°	0		
80°	0		
90°	0		
100°	0		
110°	0		
120°	0		
130°	0		
140°	0		
150°	0		
160°	0		
170°	0		
180°	0		

反射率 (%)	天井	80						70						50						30						20						0																
	壁	70		50		30		70		50		30		50		30		30		10		0		30		10		0		10		0																
室指数	固有照明率 (×0.01)																																															
0.60	94	86	85	81	80	78	92	86	84	81	80	77	83	80	79	77	78	77	75	74																												
0.80	104	95	97	91	92	88	103	94	96	90	91	88	94	89	90	87	89	87	85	84																												
1.00	107	96	100	92	94	90	105	96	98	92	94	89	96	91	92	89	91	88	86	85																												
1.25	111	98	103	95	98	92	108	97	102	94	97	91	99	93	95	91	93	90	88	87																												
1.50	113	100	106	96	101	94	111	99	104	96	100	93	101	95	97	93	95	92	90	89																												
2.00	117	102	111	99	106	97	114	101	109	98	104	96	104	97	101	95	98	94	92	91																												
2.50	119	103	114	101	109	99	116	102	111	100	107	98	106	98	103	97	100	96	94	93																												
3.00	121	104	116	102	112	100	118	103	113	101	110	99	108	99	105	98	101	97	95	94																												
4.00	124	105	120	104	116	102	120	104	116	103	113	101	110	101	108	100	103	98	97	95																												
5.00	125	106	122	105	119	104	121	105	118	104	116	103	112	102	101	105	99	98	96	96																												
10.00	129	108	127	107	126	107	124	106	123	106	122	106	115	104	114	104	108	102	101	99																												

