

# 東芝照明器具配光データシート

名称	LED高天井用照明器具
形名	LEDJ-15502N-LD9

--	--

効 率	F	1 %
	F	99 %
	F	100 %
	器具光束	17000 lm

保守率	良	0.83
	中	0.81
	否	0.77

前面	
反射面	

最大取付間隔	
A-A	1.27 H
B-B	1.27 H

備 考	
--------	--

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	358	358	358
10°	352	352	352
20°	337	337	337
30°	309	309	309
40°	266	266	266
50°	214	214	214
60°	151	151	151
70°	81	81	81
80°	21	21	21
90°	2	2	2
100°	4	4	4
110°	3	3	3
120°	1	1	1
130°	1	1	1
140°	1	1	1
150°	1	1	1
160°	1	1	1
170°	1	1	1
180°	1	1	1

反射率 (%)	天井	80						70						50						30		20		0	
	壁	70	50	30	70	50	30	70	50	30	50	30	50	30	30	10	0								
床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0								
室指数	固有照明率 (×0.01)																								
0.60	64	58	50	47	41	40	62	57	49	46	41	39	47	45	40	39	39	38	34	32					
0.80	76	69	62	58	53	51	74	68	61	58	53	51	59	56	51	50	50	49	45	43					
1.00	83	75	70	65	61	58	81	73	68	64	60	57	66	62	58	56	57	55	51	49					
1.25	91	81	78	72	69	65	88	79	77	71	68	64	73	69	66	63	64	62	58	56					
1.50	96	85	84	76	75	70	93	83	82	75	74	69	78	73	72	68	69	67	63	61					
2.00	105	91	94	84	86	79	101	89	92	83	84	78	87	81	81	76	78	75	71	69					
2.50	109	94	100	88	93	83	105	92	97	87	90	83	92	85	86	81	83	79	76	74					
3.00	113	97	104	92	98	87	108	95	101	90	95	86	96	88	91	85	87	83	80	77					
4.00	117	99	110	96	105	92	113	98	107	94	102	91	101	92	97	89	92	87	85	82					
5.00	120	101	114	98	109	95	115	100	110	97	106	94	104	94	100	92	95	90	88	85					
10.00	125	105	122	103	119	101	120	103	118	102	115	100	110	99	108	98	102	96	94	92					

