


# 東芝照明器具配光データシート

名称	LED高天井用照明器具
形名	LEDJ-20502N-LD9



効 率	F	1 %
	F	99 %
	F	100 %
	器具光束	22000 lm

保守率	良	0.83
	中	0.81
	否	0.77

前面	
反射面	

最大取付間隔	
A-A	1.27 H
B-B	1.27 H

備考	
----	--

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	357	357	357
10°	351	351	351
20°	336	336	336
30°	308	308	308
40°	267	267	267
50°	214	214	214
60°	151	151	151
70°	81	81	81
80°	20	20	20
90°	2	2	2
100°	4	4	4
110°	3	3	3
120°	1	1	1
130°	1	1	1
140°	1	1	1
150°	1	1	1
160°	1	1	1
170°	1	1	1
180°	1	1	1

反射率 (%)	天井	80			70			50			30		20	0						
	壁	70	50	30	70	50	30	50	30	30	30	10	0							
	床	30	10	30	10	30	10	30	10	30	10	30	10	0						
室指数	固有照明率 (×0.01)																			
0.60	63	58	49	47	41	40	62	57	49	46	41	39	47	45	40	39	39	38	34	32
0.80	76	69	62	58	53	51	74	68	61	57	53	51	59	56	51	50	50	49	45	43
1.00	83	75	70	65	61	58	81	73	68	64	60	57	66	62	58	56	57	55	51	49
1.25	91	81	78	72	69	65	88	79	76	71	68	64	73	69	66	63	64	62	58	56
1.50	96	85	84	76	75	70	93	83	82	75	74	69	78	73	71	68	69	67	63	61
2.00	104	91	94	84	86	78	101	89	92	83	84	78	87	81	81	76	78	75	71	69
2.50	109	94	100	88	92	83	105	92	97	87	90	82	92	85	86	81	83	79	76	74
3.00	112	96	104	91	98	87	108	95	101	90	95	86	96	88	91	84	87	83	80	77
4.00	117	99	110	95	105	92	113	98	107	94	102	91	100	92	96	89	92	87	84	82
5.00	119	101	114	98	109	95	115	100	110	97	106	94	103	94	100	92	95	90	87	85
10.00	125	105	122	103	119	101	120	103	118	102	115	100	110	99	108	98	101	96	94	92

