

東芝照明器具配光データシート

名称	LED照明器具
形名	LEDH86182PW-LD



効 率	F	10%
	F	90%
	F	100%
	器具 光束	6080 lm

保守 率	良	0.63
	中	0.60
	否	0.56

前面	カバー (乳白)
反射面	塗装 (白)

最大取付間隔	
A-A	1.3 H
B-B	1.3 H

備考	
----	--

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	270	270	270
10°	267	267	267
20°	256	256	256
30°	239	239	239
40°	213	213	213
50°	180	180	180
60°	141	141	141
70°	98	98	98
80°	59	59	59
90°	30	30	30
100°	18	18	18
110°	15	15	15
120°	13	13	13
130°	13	13	13
140°	14	14	14
150°	14	14	14
160°	13	13	13
170°	14	14	14
180°	14	14	14

反射率 (%)	天井	80						70						50						30		20		0	
	壁	70		50		30		70		50		30		50		30		30		10		0			
床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0	0	
室指数	固有照明率 (×0.01)																								
0.60	59	54	44	42	36	34	56	52	43	41	35	34	41	39	34	33	32	32	27	25					
0.80	70	64	56	52	46	44	68	62	54	51	45	44	51	49	43	42	42	41	36	33					
1.00	78	70	63	59	53	51	74	67	61	57	52	50	57	54	50	48	47	46	41	38					
1.25	85	76	71	65	62	58	81	73	69	64	60	57	65	61	57	55	54	52	47	44					
1.50	90	79	77	70	68	63	86	77	74	68	66	61	69	65	62	59	59	57	52	49					
2.00	99	86	87	78	78	71	94	83	84	76	76	70	78	72	71	67	67	64	60	56					
2.50	103	89	93	82	85	76	98	87	89	80	82	75	83	76	77	72	72	69	64	61					
3.00	107	92	98	86	90	80	102	89	94	84	87	79	87	80	81	75	76	72	68	65					
4.00	112	95	104	90	98	86	106	93	100	88	94	84	92	84	87	81	81	77	73	70					
5.00	115	97	108	93	102	89	109	94	103	91	98	87	95	87	91	84	84	80	76	73					
10.00	121	101	117	99	114	97	115	99	112	97	109	95	102	92	100	91	92	87	84	80					

