


東芝照明器具配光データシート

名称	LED照明器具
形名	LEDH86274PL-LD



効 率	F	9 %
	F	91 %
	F	100 %
	器具 光束	5510 lm

保守 率	良	0.63
	中	0.60
	否	0.56

前面	カバー (乳白)
反射面	塗装 (白)

最大取付間隔	
A-A	1.3 H
B-B	1.3 H

備考	
----	--

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	265	265	265
10°	262	262	262
20°	253	253	253
30°	237	237	237
40°	214	214	214
50°	183	183	183
60°	144	144	144
70°	102	102	102
80°	63	63	63
90°	33	33	33
100°	17	17	17
110°	10	10	10
120°	9	9	9
130°	11	11	11
140°	12	12	12
150°	12	12	12
160°	12	12	12
170°	14	14	14
180°	14	14	14

反射率 (%)	天井	80			70			50			30		20	0						
	壁	70	50	30	70	50	30	50	30	30	30	10	0							
床	30	10	30	10	30	10	30	10	30	10	30	10	0							
室指数	固有照明率 (×0.01)																			
0.60	59	54	44	42	35	34	56	52	43	41	34	33	41	39	33	32	32	31	27	25
0.80	70	64	55	52	46	44	67	62	54	51	45	43	51	48	43	42	41	40	36	33
1.00	77	69	63	58	53	50	74	67	61	57	52	49	57	54	49	48	47	46	41	38
1.25	85	76	71	65	61	57	81	73	69	64	60	56	64	61	57	54	54	52	47	44
1.50	90	79	77	70	67	62	86	77	74	68	65	61	69	65	62	59	59	57	52	49
2.00	98	86	87	78	78	71	94	83	84	76	75	70	78	72	71	67	67	65	60	56
2.50	103	89	93	82	84	76	99	87	89	80	82	75	83	76	77	72	72	69	64	61
3.00	107	92	98	85	90	80	102	89	94	84	87	78	87	80	81	76	76	73	68	65
4.00	112	95	104	90	97	85	107	93	100	88	94	84	92	84	87	81	81	78	74	70
5.00	115	97	108	93	102	89	109	95	104	91	98	87	95	87	91	84	85	81	77	73
10.00	121	101	117	99	114	97	116	99	112	97	109	95	103	93	100	91	93	87	84	81

