

東芝照明器具配光データシート

名称	LED照明器具
形名	LEDB87910L-LS



効 率	F	28%
	F	72%
	F	100%
	器具 光束	575 lm

保守 率	良	0.63
	中	0.60
	否	0.56

前面	
反射面	

最大取付間隔	
A-A	1.4 H
B-B	1.4 H

備考	
----	--

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	155	155	155
10°	155	155	155
20°	155	155	155
30°	150	151	155
40°	140	140	145
50°	128	130	137
60°	112	114	123
70°	93	96	106
80°	74	76	88
90°	53	56	68
100°	52	53	65
110°	48	49	60
120°	43	45	54
130°	36	38	47
140°	30	31	40
150°	25	25	33
160°	19	18	23
170°	9	9	11
180°	1	1	1

反射率 (%)	天井	80						70						50						30		20		0	
	壁	70	50	30	70	50	30	70	50	30	50	30	50	30	30	10	0	10	0						
床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30						
室指数	固有照明率 (×0.01)																								
0.60	54	49	39	37	30	29	50	47	37	35	29	28	33	32	26	25	24	23	18	15					
0.80	64	58	49	46	39	38	60	55	47	44	38	36	42	40	34	33	31	30	25	21					
1.00	71	64	56	52	46	44	66	60	53	50	44	42	47	45	40	38	36	35	29	25					
1.25	79	70	64	59	54	50	73	66	60	56	51	48	54	50	46	44	41	40	34	29					
1.50	84	74	70	63	59	55	78	70	66	60	56	53	58	54	51	48	45	44	38	33					
2.00	92	80	79	71	70	64	86	76	75	68	66	61	66	61	59	56	52	50	44	39					
2.50	97	84	86	76	76	69	90	79	80	72	72	66	71	65	64	60	57	55	49	43					
3.00	101	86	90	79	82	73	94	82	85	75	77	70	74	68	68	64	61	58	52	46					
4.00	106	90	97	84	90	79	98	85	91	80	84	75	79	73	74	69	66	63	57	50					
5.00	109	92	101	87	95	82	101	88	95	83	89	79	83	75	78	72	69	65	60	53					
10.00	116	97	111	94	107	91	108	92	104	90	100	87	91	82	88	80	77	73	68	61					

