

東芝照明器具配光データシート

名称	LED照明器具
形名	LEDB87921YL (K) -LS



効 率	F	0 %
	F	100 %
	F	100 %
	器具 光束	355 lm

保守 率	良	0.63
	中	0.60
	否	0.56

前面	
反射面	

最大取付間隔	
A-A	1.3 H
B-B	1.3 H

備考	
----	--

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	340	340	340
10°	334	335	335
20°	317	320	319
30°	289	295	293
40°	251	259	256
50°	205	213	210
60°	151	159	156
70°	93	100	96
80°	35	42	38
90°	0	1	0
100°	0	0	0
110°	0	0	0
120°	0	0	0
130°	0	0	0
140°	0	0	0
150°	0	0	0
160°	0	0	0
170°	0	0	0
180°	1	0	1

反射率 (%)	天井	80			70			50			30		20	0						
	壁	70	50	30	70	50	30	50	30	30	30	10	0							
	床	30	10	30	10	30	10	30	10	30	10	30	10	0						
室指数	固有照明率 (×0.01)																			
0.60	62	57	48	45	39	38	60	56	47	45	39	38	46	44	38	37	38	37	32	31
0.80	74	68	60	56	51	49	72	66	59	56	50	49	57	54	49	48	48	47	43	41
1.00	82	73	68	63	58	55	79	72	66	62	58	55	64	60	56	54	55	53	49	47
1.25	89	79	76	70	67	63	87	78	75	69	66	62	71	67	64	61	62	60	56	54
1.50	94	83	82	75	73	68	91	82	80	74	72	67	76	72	69	66	67	65	61	59
2.00	103	90	92	82	84	76	99	88	90	81	82	76	85	79	79	74	76	73	69	67
2.50	108	93	98	87	90	81	104	91	95	86	88	81	90	83	85	79	81	78	74	72
3.00	111	95	103	90	96	85	107	94	100	89	93	85	94	87	89	83	85	81	78	76
4.00	116	98	109	94	103	91	112	97	106	93	100	90	99	91	95	88	91	86	83	81
5.00	119	100	113	97	108	94	114	99	109	96	105	93	103	93	99	91	94	89	87	85
10.00	124	104	121	102	118	101	120	103	117	101	114	100	109	99	107	97	101	96	94	92

