

# 東芝照明器具配光データシート

名称	
形名	LEDB87923YL (K) -LS


効 率	F	0 %
	F	100 %
	F	100 %
	器具 光束	360 lm

保守 率	良	0.63
	中	0.60
	否	0.56

前面	
反射面	

最大取付間隔	
A-A	1.3 H
B-B	1.3 H

備考	
----	--

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	338	342	342
10°	335	337	338
20°	320	320	323
30°	293	292	297
40°	256	253	259
50°	210	206	211
60°	158	152	157
70°	100	93	99
80°	42	35	40
90°	1	0	0
100°	0	0	0
110°	0	0	0
120°	0	0	0
130°	0	0	0
140°	0	0	0
150°	0	0	0
160°	0	0	0
170°	0	0	0
180°	1	1	1

反射率 (%)	天井	80						70						50						30		20		0
	壁	70		50		30		70		50		30		50		30		30		10		0		
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0		
室指数	固有照明率 (×0.01)																							
0.60	63	58	48	46	40	38	61	56	47	45	39	38	46	44	39	38	38	37	33	31				
0.80	75	68	61	57	51	49	73	67	59	56	51	49	57	55	50	48	49	48	43	41				
1.00	82	74	68	63	59	56	80	72	67	62	58	55	64	61	57	54	55	54	49	47				
1.25	90	80	77	70	67	63	87	78	75	69	66	63	72	68	64	62	62	61	56	54				
1.50	95	84	83	75	73	68	92	82	81	74	72	68	77	72	70	66	68	65	61	59				
2.00	104	90	93	83	84	77	100	88	90	82	82	76	86	80	79	75	76	74	70	67				
2.50	108	93	99	87	91	82	104	92	96	86	89	81	91	84	85	80	82	78	75	73				
3.00	112	96	103	91	96	86	108	94	100	89	94	85	95	87	90	83	86	82	79	76				
4.00	117	99	110	95	104	91	112	98	106	94	101	90	100	92	96	89	91	87	84	82				
5.00	119	101	114	97	108	94	115	100	110	96	105	93	103	94	100	92	94	90	87	85				
10.00	125	105	122	103	119	101	121	103	118	102	115	100	110	99	108	98	102	96	94	92				

