

東芝照明器具配光データシート

名称	LED照明器具
形名	LEDB87926YL-LS



効 率	F	11 %
	F	89 %
	F	100 %
	器具 光束	670 lm

保守 率	良	0.67
	中	0.63
	否	0.56

前面	
反射面	

最大取付間隔	
A-A	1.4 H
B-B	1.4 H

備考	
----	--

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	232		
10°	235		
20°	242		
30°	228		
40°	208		
50°	174		
60°	138		
70°	101		
80°	69		
90°	46		
100°	29		
110°	19		
120°	14		
130°	10		
140°	7		
150°	5		
160°	3		
170°	2		
180°	0		

反射率 (%)	天井	80						70						50						30		20		0	
	壁	70	50	30	70	50	30	70	50	30	50	30	50	30	30	10	0								
床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0								
室指数	固有照明率 (×0.01)																								
0.60	58	53	43	41	34	33	55	51	42	40	33	32	39	38	32	31	31	30	25	23					
0.80	69	63	54	51	45	43	66	61	53	50	44	42	49	47	42	40	40	39	34	31					
1.00	76	68	62	57	52	49	73	66	60	56	50	48	56	53	48	46	46	44	39	36					
1.25	84	75	70	64	60	56	80	72	67	62	58	55	63	59	55	53	52	51	45	42					
1.50	89	78	76	69	66	61	85	76	73	67	64	60	68	63	60	57	57	55	50	47					
2.00	97	85	85	76	76	69	93	82	82	74	74	68	76	71	69	65	65	62	57	54					
2.50	102	88	91	81	83	75	97	85	88	79	80	73	81	75	75	70	70	67	62	59					
3.00	106	91	96	84	88	79	101	88	92	82	85	77	85	78	79	74	74	70	66	62					
4.00	111	94	103	89	96	84	105	91	98	87	92	82	90	82	85	79	79	75	71	67					
5.00	114	96	107	92	101	87	108	93	102	89	97	86	93	85	89	82	82	78	74	70					
10.00	120	100	116	98	112	95	114	98	111	96	107	93	101	91	98	89	90	85	82	78					

