

東芝照明器具配光データシート

名称	LED照明器具
形名	LEDB87932YL-LS



効 率	F	26%
	F	74%
	F	100%
	器具 光束	575 lm

保 守 率	良	0.63
	中	0.60
	否	0.56

前面	
反射面	

最大取付間隔	
A-A	1.3 H
B-B	1.4 H

備考	
----	--

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	184	184	184
10°	182	182	181
20°	177	178	177
30°	168	169	169
40°	149	156	156
50°	125	137	136
60°	104	113	112
70°	82	85	88
80°	151	56	68
90°	82	45	60
100°	70	44	61
110°	82	42	54
120°	71	39	42
130°	37	34	32
140°	17	27	24
150°	11	20	16
160°	8	13	9
170°	4	5	4
180°	3	5	3

反射率 (%)	天井	80						70						50						30		20		0	
	壁	70	50	30	70	50	30	70	50	30	50	30	50	30	30	10	0	10	0						
床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0						
室指数	固有照明率 (×0.01)																								
0.60	55	50	40	38	31	30	51	47	38	36	30	29	35	33	28	27	25	25	20	17					
0.80	65	59	50	47	41	39	61	56	48	45	39	38	43	41	36	35	33	32	27	23					
1.00	72	65	57	53	47	45	67	61	54	51	45	43	49	46	41	40	38	37	31	27					
1.25	79	70	65	60	55	52	74	67	62	57	52	50	55	52	48	46	43	42	36	32					
1.50	84	74	71	64	61	56	79	70	67	61	58	54	59	56	52	50	47	46	40	35					
2.00	92	80	80	71	70	64	86	76	75	68	67	62	67	62	60	57	54	52	46	41					
2.50	97	84	86	76	77	69	90	79	81	73	73	67	72	66	65	61	58	56	50	45					
3.00	101	86	91	79	82	73	94	82	85	76	78	70	75	69	69	65	62	59	54	48					
4.00	105	90	97	84	90	79	98	85	91	80	85	76	80	73	75	69	67	64	58	52					
5.00	108	92	101	87	95	82	101	87	95	83	89	79	83	76	79	73	70	66	61	55					
10.00	115	96	111	93	107	91	107	92	104	90	100	87	91	82	88	80	78	73	69	62					

