

# 東芝ランプ 配光データシート

名称	東芝LED電球
形名	LDA5L-G-E17 /S/D40W
光束	440 lm × 1

保守率	良	1.00
	中	1.00
	否	1.00



効率	F		%
	F		%
	F	100	%
	器具光束	440	lm

最大取付間隔	
A-A	1.53 H
B-B	1.53 H

備考

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	152		
10°	152		
20°	153		
30°	152		
40°	150		
50°	144		
60°	134		
70°	119		
80°	101		
90°	80		
100°	59		
110°	41		
120°	26		
130°	16		
140°	9		
150°	5		
160°	2		
170°	0		
180°	0		

反射率 (%)	天井	80						70						50						30						20						0					
	壁	70		50		30		70		50		30		50		30		30		10		30		10		10		0									
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10								
室指数	照明率 (×0.01)																																				
0.60	52	47	36	34	27	26	49	45	35	33	26	25	31	30	24	23	22	22	16	14																	
0.80	61	56	46	43	35	34	58	53	43	41	34	33	39	38	31	30	29	28	23	19																	
1.00	70	63	54	50	43	41	66	60	51	48	41	40	46	44	38	37	35	34	28	24																	
1.25	77	68	62	56	51	48	72	65	59	54	49	46	53	50	45	43	41	39	33	29																	
1.50	83	73	68	62	57	53	77	69	64	59	55	51	58	54	50	47	46	44	38	34																	
2.00	91	79	78	69	67	61	85	75	73	66	64	59	66	61	58	55	53	51	45	40																	
2.50	96	83	84	74	74	67	90	79	79	71	71	65	71	66	64	60	58	56	50	45																	
3.00	100	86	89	78	80	71	94	82	84	75	76	69	75	69	69	64	62	59	54	49																	
4.00	105	89	96	83	88	77	99	86	90	80	83	74	81	74	75	69	68	64	59	54																	
5.00	108	92	100	86	93	81	102	88	95	83	88	78	84	77	79	73	71	68	63	57																	
10.00	116	97	111	94	106	90	109	93	105	90	100	87	93	84	90	82	80	76	71	66																	

