




# ■ 東芝ランプ 配光データシート

名称	東芝LED電球
形名	LDA11N-G/10OW
光束	1520 lm × 1

保守率	良	1.00
	中	1.00
	否	1.00

--	--

効 率	F 	%
	F 	%
	F 	100 %
	器具 光束	1520 lm

最大取付間隔	
A-A	1.5 H
B-B	1.5 H

備考	
----	--

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	115		
10°	115		
20°	114		
30°	114		
40°	113		
50°	110		
60°	106		
70°	101		
80°	94		
90°	86		
100°	78		
110°	68		
120°	59		
130°	49		
140°	40		
150°	32		
160°	25		
170°	18		
180°	0		

反射率 (%)	天井		80				70				50				30		20		0												
	壁	床	70		50		70		50		70		50		30		10		0												
			30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30
室指数		照 明 率 (×0.01)																													
0.60		51	47	37	35	28	27	48	44	34	33	26	25	30	29	23	22	20	20	15	11										
0.80		62	56	46	43	36	35	57	52	43	41	34	33	38	36	30	29	26	26	20	16										
1.00		68	61	53	49	43	41	63	57	50	46	40	38	43	41	35	34	31	30	24	19										
1.25		76	67	61	56	50	47	70	63	57	52	47	45	49	46	41	40	36	35	28	23										
1.50		81	71	66	60	56	52	74	66	62	57	52	49	53	50	46	43	39	38	32	26										
2.00		89	77	76	68	66	60	82	72	71	64	61	57	61	56	53	50	46	44	38	31										
2.50		94	81	82	72	72	65	86	76	76	68	68	62	65	60	59	55	50	48	42	35										
3.00		98	84	87	76	78	69	90	79	81	72	73	66	69	63	63	58	54	51	45	38										
4.00		103	87	94	81	86	75	95	82	87	76	80	71	74	68	69	63	59	56	50	42										
5.00		106	90	98	84	91	79	98	84	91	79	84	75	77	70	73	67	62	59	53	45										
10.00		113	95	108	91	104	88	104	90	100	87	96	84	85	77	82	75	70	66	60	52										

