

東芝照明器具配光データシート

名称	東芝LED器具
形名	LEKT427193TN-LS2



効 率	F	1 %
	F	99 %
	F	100 %
	器具 光束	18800 lm

保 守 率	良	0.81
	中	0.77
	否	0.68

前面	カバー (乳白)
反射面	塗装 (白)

最大取付間隔	
A-A	1.3 H
B-B	1.3 H

備考

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	325	325	325
10°	320	319	320
20°	306	302	304
30°	284	274	279
40°	252	239	245
50°	216	196	206
60°	169	147	161
70°	115	93	110
80°	47	37	51
90°	0	2	3
100°	0	2	2
110°	0	2	1
120°	0	2	1
130°	0	1	1
140°	0	1	1
150°	0	1	0
160°	0	1	0
170°	1	1	0
180°	1	1	1

反 射 率 (%)	天井	80						70						50						30		20		0	
	壁	70		50		30		70		50		30		50		30		30		10		0			
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0		
室指数		固有照明率 ($\times 0.01$)																							
0.60	61	56	47	45	38	37	60	55	46	44	38	37	45	43	37	36	36	36	31	29					
0.80	74	67	59	55	50	48	71	65	58	55	49	47	56	53	48	46	47	46	41	39					
1.00	81	73	67	62	57	54	78	71	65	61	56	54	62	59	55	53	53	52	47	45					
1.25	89	79	75	69	65	61	86	77	73	68	64	61	70	66	62	60	60	59	54	52					
1.50	94	83	81	74	72	66	90	81	79	72	70	66	75	70	68	65	66	64	59	57					
2.00	102	89	91	81	82	75	99	87	89	80	81	74	84	78	77	73	74	72	68	65					
2.50	107	92	97	86	89	80	103	91	94	85	87	80	89	82	83	78	80	77	73	70					
3.00	111	95	102	89	95	84	107	93	99	88	92	84	93	86	88	82	84	80	77	75					
4.00	116	98	108	94	102	90	111	97	105	93	99	89	99	90	94	87	90	85	82	80					
5.00	118	100	112	97	107	93	114	99	109	95	104	92	102	93	98	90	93	88	86	83					
10.00	125	104	121	102	118	100	120	103	117	101	114	99	109	99	107	97	101	95	93	91					

