

# 東芝照明器具配光データシート

名称	LED高天井用照明器具
形名	LEDJ-10019N-LD9

--	--

効 率	F	0 %
	F	100 %
	F	100 %
	器具光束	15300 lm

保守率	良	0.86
	中	0.81
	否	0.72

前面	下面開放
反射面	レンズ (広角)

最大取付間隔	
A-A	1.3 H
B-B	1.3 H

備考	
----	--

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	488		
10°	493		
20°	464		
30°	431		
40°	338		
50°	158		
60°	81		
70°	31		
80°	3		
90°	0		
100°	0		
110°	0		
120°	0		
130°	0		
140°	1		
150°	1		
160°	1		
170°	1		
180°	1		

反射率 (%)	天井	80						70						50						30						20						0					
	壁	70		50		30		70		50		30		50		30		30		10		30		10		10		0									
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10								
室指数	固有照明率 (×0.01)																																				
0.60	72	66	60	57	52	50	70	65	59	56	52	50	57	55	51	50	50	49	46	44																	
0.80	85	77	73	68	65	63	83	76	72	68	65	62	70	67	64	62	62	61	57	56																	
1.00	91	82	80	74	72	68	89	81	79	73	71	68	76	72	70	67	68	67	63	61																	
1.25	98	87	88	80	80	75	96	86	86	80	79	74	83	78	77	74	75	73	69	68																	
1.50	103	91	93	84	85	79	100	89	91	83	84	79	87	82	82	78	79	77	74	72																	
2.00	110	96	101	91	95	86	107	94	99	90	93	86	95	88	90	85	87	83	80	79																	
2.50	114	98	106	94	100	90	110	97	103	93	98	89	98	91	94	88	90	87	84	82																	
3.00	116	100	110	96	104	93	113	99	107	95	102	92	101	93	97	91	93	89	87	85																	
4.00	120	102	115	99	110	97	116	101	111	98	107	96	105	96	102	94	97	93	90	89																	
5.00	122	103	118	101	113	99	118	102	114	100	110	98	107	98	105	96	99	94	92	91																	
10.00	126	106	124	104	121	103	122	104	120	103	117	102	112	101	110	100	104	98	97	95																	

