

# 東芝照明器具配光データシート

名称	LED高天井用照明器具
形名	LEDJ-10026N-LD9

--	--

効 率	F	0 %
	F	100 %
	F	100 %
	器具光束	10800 lm

保守率	良	0.86
	中	0.81
	否	0.72

前面	下面開放
反射面	レンズ (中角)

最大取付間隔	
A-A	0.8 H
B-B	0.8 H

備考	
----	--

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	1094	1094	1094
10°	1001	1001	1001
20°	758	758	758
30°	409	409	409
40°	173	173	173
50°	85	85	85
60°	48	48	48
70°	25	25	25
80°	9	9	9
90°	0	0	0
100°	0	0	0
110°	0	0	0
120°	0	0	0
130°	0	0	0
140°	1	1	1
150°	1	1	1
160°	2	2	2
170°	3	3	3
180°	3	3	3

反射率 (%)	天井	80						70						50						30		20		0
	壁	70		50		30		70		50		30		50		30		30		10		0		
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0	0	
室指数	固有照明率 (×0.01)																							
0.60	85	78	75	71	69	66	83	77	74	71	68	66	73	70	67	66	67	65	63	62				
0.80	96	87	86	81	80	77	94	86	85	81	80	77	83	80	78	76	77	76	73	72				
1.00	100	90	91	84	84	80	98	89	89	84	84	80	87	82	82	79	80	78	76	75				
1.25	105	93	96	88	89	84	102	92	94	87	88	83	91	86	86	82	84	82	79	78				
1.50	108	95	100	90	93	87	105	94	98	90	92	86	94	88	89	85	87	84	82	80				
2.00	113	99	106	95	100	91	110	97	103	94	98	91	99	92	95	89	92	88	86	84				
2.50	116	100	110	97	104	94	113	99	107	96	102	93	102	94	98	92	94	91	88	87				
3.00	119	102	113	99	108	96	115	100	110	98	105	95	104	96	101	94	97	92	90	89				
4.00	122	103	117	101	113	99	118	102	114	100	110	98	107	98	105	97	100	95	93	91				
5.00	124	105	120	103	116	101	119	103	116	102	113	100	109	100	107	98	102	97	95	93				
10.00	128	107	126	106	124	105	123	106	121	105	120	104	114	103	113	102	106	100	99	97				

